



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'APR.3pm'***

**\$ man APR.3pm**

libapache2-mod-perl2-2.0.12::doUserContributed)Plibapache2-mod-perl2-2.0.12::docs::api::APR(3pm)

#### NAME

APR - Perl Interface for Apache Portable Runtime (libapr and libaprutil Libraries)

#### Synopsis

```
use APR ();
```

#### Description

On load this modules prepares the APR environment (initializes memory pools, data structures, etc.)

You don't need to use this module explicitly, since it's already loaded internally by all "APR::\*" modules.

#### Using APR modules outside mod\_perl 2.0

You'd use the "APR::\*" modules outside mod\_perl 2.0, just like you'd use it with mod\_perl 2.0. For example to get a random unique string you could call:

```
% perl -MAPR::UUID -le 'print APR::UUID->new->format'
```

#### See Also

mod\_perl 2.0 documentation.

## Copyright

mod\_perl 2.0 and its core modules are copyrighted under The Apache Software License,  
Version 2.0.

## Authors

The mod\_perl development team and numerous contributors.

perl v5.34.0

2022-libapache2-mod-perl2-2.0.12::docs::api::APR(3pm)