



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'Apache2::Command.3pm'***

#### ***\$ man Apache2::Command.3pm***

libapache2-mod-perl2-2.0.12::doUseralibapache2-mod-perl2-2.0.12::docs::api::Apache2::Command(3pm)

#### NAME

Apache2::Command - Perl API for accessing Apache module command information

#### Synopsis

```
use Apache2::Module ();
use Apache2::Command ();

my $module = Apache2::Module::find_linked_module('mod_perl.c');
for (my $cmd = $module->cmds; $cmd; $cmd = $cmd->next) {
    $cmd->args_how();
    $cmd->errmsg();
    $cmd->name();
    $cmd->req_override();
}
```

#### Description

"Apache2::Command" provides the Perl API for accessing Apache module command information

#### API

"Apache2::Command" provides the following functions and/or methods:

##### "args\_how"

What the command expects as arguments:

```
$how = $cmd->args_how();
```

obj: \$cmd ( "Apache2::Command object" )

ret: \$how ( "Apache2::Const :cmd\_how constant" )

The flag value representing the type of this command (i.e. "Apache2::Const::ITERATE",

"Apache2::Const::TAKE2").

since: 2.0.00

"errmsg"

Get usage message for that command, in case of syntax errors:

```
$error = $cmd->errmsg();
```

obj: \$cmd ( "Apache2::Command object" )

ret: \$error ( string )

The error message

since: 2.0.00

"name"

Get the name of this command:

```
$name = $cmd->name();
```

obj: \$cmd ( "Apache2::Command object" )

ret: \$name ( string )

The command name

since: 2.0.00

"next"

Get the next command in the chain of commands for this module:

```
$next = $cmd->next();
```

obj: \$cmd ( "Apache2::Command object" )

ret: \$next ( "Apache2::Command object" )

Returns the next command in the chain for this module, "undef" for the last command.

since: 2.0.00

"req\_override"

What overrides need to be allowed to enable this command:

```
$override = $cmd->req_override
```

obj: \$cmd ( "Apache2::Command object" )

ret: \$override ( "Apache2::Const :override constant" )

The bit mask representing the overrides this command is allowed in (i.e

"Apache2::Const::OR\_ALL"/"Apache2::Const::ACCESS\_CONF").

since: 2.0.00

For example:

```
use Apache2::Const -compile => qw(:override);
```

```
$cmd->req_override() & Apache2::Const::OR_AUTHCFG;
```

```
$cmd->req_override() & Apache2::Const::OR_LIMIT;
```

#### See Also

[mod\\_perl 2.0 documentation.](#)

#### Copyright

mod\_perl 2.0 and its core modules are copyrighted under The Apache Software License,

Version 2.0.

#### Authors

The mod\_perl development team and numerous contributors.

perl v5.34.0

libapache2-mod-perl2-2.0.12::docs::api::Apache2::Command(3pm)