



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Apache::Session::MySQL.3pm'

\$ man Apache::Session::MySQL.3pm

Apache::Session::MySQL(3pm) User Contributed Perl Documentation Apache::Session::MySQL(3pm)

NAME

Apache::Session::MySQL - An implementation of Apache::Session

SYNOPSIS

```
use Apache::Session::MySQL;
```

```
#if you want Apache::Session to open new DB handles:
```

```
tie %hash, 'Apache::Session::MySQL', $id, {  
    DataSource => 'dbi:mysql:sessions',  
    UserName   => $db_user,  
    Password   => $db_pass,  
    LockDataSource => 'dbi:mysql:sessions',  
    LockUserName => $db_user,  
    LockPassword => $db_pass  
};
```

```
#or, if your handles are already opened:
```

```
tie %hash, 'Apache::Session::MySQL', $id, {  
    Handle   => $dbh,
```

```
LockHandle => $dbh
```

```
};
```

DESCRIPTION

This module is an implementation of `Apache::Session`. It uses the MySQL backing store and the MySQL locking scheme. See the example, and the documentation for `Apache::Session::Store::MySQL` and `Apache::Session::Lock::MySQL` for more details.

AUTHOR

This module was written by Jeffrey William Baker <jwbaker@acm.org>.

SEE ALSO

`Apache::Session::File`, `Apache::Session::Flex`, `Apache::Session::DB_File`,
`Apache::Session::Postgres`, `Apache::Session`

perl v5.30.3

2020-09-20

`Apache::Session::MySQL(3pm)`