



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Apache::Session::MySQL::NoLock.3pm'

\$ man Apache::Session::MySQL::NoLock.3pm

Apache::Session::MySQL::NoLock(User Contributed Perl DocumentaApache::Session::MySQL::NoLock(3pm)

NAME

Apache::Session::MySQL::NoLock - An implementation of Apache::Session::MySQL without locking

SYNOPSIS

```
use Apache::Session::MySQL::NoLock;
```

```
#if you want Apache::Session to open new DB handles:
```

```
tie %hash, 'Apache::Session::MySQL::NoLock', $id, {  
    DataSource => 'dbi:mysql:sessions',  
    UserName => $db_user,  
    Password => $db_pass,  
};
```

```
#or, if your handles are already opened:
```

```
tie %hash, 'Apache::Session::MySQL::NoLock', $id, {  
    Handle => $dbh,  
};
```

To configure the non-locking session store in RT (what I use this module for),
put the following into your C<RT_SiteConfig.pm> module:

```
Set($WebSessionClass , 'Apache::Session::MySQL::NoLock');
```

DESCRIPTION

This module is an implementation of Apache::Session. It uses the MySQL backing store and the Null locking scheme. See the example, and the documentation for Apache::Session::Store::MySQL for more details.

WARNING

This module explicitly DOES NOT DO ANY LOCKING. This can cause your session data to be overwritten or stale data to be read by subsequent requests.

This CAN CAUSE LARGE PROBLEMS IN YOUR APPLICATION.

AUTHOR

This module was written by Tomas Doran <bobtfish@bobtfish.net>.

SEE ALSO

Apache::Session::MySQL, Apache::Session::Flex, Apache::Session

perl v5.30.3

2020-09-20

Apache::Session::MySQL::NoLock(3pm)