



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Apache::Session::Postgres.3pm'

\$ man Apache::Session::Postgres.3pm

Apache::Session::Postgres(3pm) User Contributed Perl Documentation Apache::Session::Postgres(3pm)

NAME

Apache::Session::Postgres - An implementation of Apache::Session

SYNOPSIS

```
use Apache::Session::Postgres;

#if you want Apache::Session to open new DB handles:

tie %hash, 'Apache::Session::Postgres', $id, {
    DataSource => 'dbi:Pg:dbname=sessions',
    UserName   => $db_user,
    Password   => $db_pass,
    Commit     => 1
};

#or, if your handles are already opened:

tie %hash, 'Apache::Session::Postgres', $id, {
    Handle => $dbh,
    Commit => 1
};
```

DESCRIPTION

This module is an implementation of Apache::Session. It uses the Postgres backing store and no locking. See the example, and the documentation for Apache::Session::Store::Postgres for more details.

USAGE

The special Apache::Session argument for this module is Commit. You MUST provide the

Commit argument, which instructs this module to either commit the transaction when it is finished, or to simply do nothing. This feature is provided so that this module will not have adverse interactions with your local transaction policy, nor your local database handle caching policy. The argument is mandatory in order to make you think about this problem.

AUTHOR

This module was written by Jeffrey William Baker <jwbaker@acm.org>.

SEE ALSO

Apache::Session::File, Apache::Session::Flex, Apache::Session::DB_File,

Apache::Session::Postgres, Apache::Session

perl v5.30.3

2020-09-20

Apache::Session::Postgres(3pm)