



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'AptPkg::hash.3pm'***

***\$ man AptPkg::hash.3pm***

AptPkg::hash(3pm)      User Contributed Perl Documentation      AptPkg::hash(3pm)

**NAME**

AptPkg::hash - a helper class for implementing tied hashes

**SYNOPSIS**

use AptPkg::hash;

**DESCRIPTION**

The AptPkg::hash class provides hash-like access for objects which have an underlying XS implementation.

Such objects need to add AptPkg::hash to @ISA, provide get, set and exists methods, and an iterator class.

AptPkg::hash

new([XS\_OBJECT])

Create a object as a tied hash. The object is implemented as a hash reference blessed into the class, which in turn is tied to AptPkg::hash.

This means that both \$obj->method() and \$obj->{key} valid, the latter invoking get/set (through FETCH/STORE).

The tie associates an array reference with the hash, which initially contains a reference to the hash, the XS object and an anon hash which may be used by subclasses to store state information.

If no XS object is passed, one is created via `new` in the XS class. The name of that class is constructed from the class name, by lower-casing the last component and prefixing it with an underscore (eg. `AptPkg::Config` becomes `AptPkg::_config`).

If the module contains a `@KEYS` array, then the private hash will be populated with those entries as keys (see the description below of the `AptPkg::hash::method` class).

`_self, _xs, _priv`

Accessors which may be used in subclass methods to fetch the three array elements associated with the hash reference.

`keys(ARGS)`

In a scalar context, creates and returns a new iterator object (the class name with the suffix `::Iter` appended).

The XS object, the private hash and any arguments are passed to the constructor.

In an array context, the iterator is used to generate a list of keys which are then returned.

The iterator class must implement a `next` method, which returns the current key and advances to the next.

`AptPkg::hash::method`

The `AptPkg::hash::method` class extends `AptPkg::hash`, providing a simple way to map a fixed set of keys (defined by the `@KEYS` array) into method calls on either the object, or the internal XS object.

Classes inheriting from `AptPkg::hash::method` should provide an iterator class which

inherits from AptPkg::hash::method::iter.

AUTHOR

Brendan O'Dea <bod@debian.org>

perl v5.34.0

2022-02-06

AptPkg::hash(3pm)