



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Authen::SASL::Perl::ANONYMOUS.3pm'

\$ man Authen::SASL::Perl::ANONYMOUS.3pm

Authen::SASL::Perl::ANONYMOUS(3User Contributed Perl DocumentatAuthen::SASL::Perl::ANONYMOUS(3pm)

NAME

Authen::SASL::Perl::ANONYMOUS - Anonymous Authentication class

SYNOPSIS

```
use Authen::SASL qw(Perl);

$sasl = Authen::SASL->new(
    mechanism => 'ANONYMOUS',
    callback => {
        authname => $mailaddress
    },
);
```

DESCRIPTION

This method implements the client part of the ANONYMOUS SASL algorithm, as described in RFC 2245 resp. in IETF Draft draft-ietf-sasl-anon-XX.txt.

CALLBACK

The callbacks used are:

authname

email address or UTF-8 encoded string to be used as trace information for the server

SEE ALSO

Authen::SASL, Authen::SASL::Perl

AUTHORS

Software written by Graham Barr <gbarr@pobox.com>, documentation written by Peter Marschall <peter@adpm.de>.

Please report any bugs, or post any suggestions, to the perl-ldap mailing list <perl-ldap@perl.org>

COPYRIGHT

Copyright (c) 2002-2004 Graham Barr. All rights reserved. This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

Documentation Copyright (c) 2004 Peter Marschall. All rights reserved. This documentation is distributed, and may be redistributed, under the same terms as Perl itself.

perl v5.32.0

2020-12-18

Authen::SASL::Perl::ANONYMOUS(3pm)