



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'CPAN::Plugin::Specfile.3perl'

\$ man CPAN::Plugin::Specfile.3perl

CPAN::Plugin::Specfile(3perl) Perl Programmers Reference Guide CPAN::Plugin::Specfile(3perl)

NAME

CPAN::Plugin::Specfile - Proof of concept implementation of a trivial CPAN::Plugin

SYNOPSIS

```
# once in the cpan shell
o conf plugin_list push CPAN::Plugin::Specfile
# make permanent
o conf commit
# any time in the cpan shell to write a spec file
test Acme::Meta
# disable
# if it is the last in plugin_list:
o conf plugin_list pop
# otherwise, determine the index to splice:
o conf plugin_list
# and then use splice, e.g. to splice position 3:
o conf plugin_list splice 3 1
```

DESCRIPTION

Implemented as a post-test hook, this plugin writes a specfile after every successful test run. The content is also written to the terminal.

As a side effect, the timestamps of the written specfiles reflect the linear order of all dependencies.

WARNING: This code is just a small demo how to use the plugin system of the CPAN shell,

not a full fledged spec file writer. Do not expect new features in this plugin.

OPTIONS

The target directory to store the spec files in can be set using "dir" as in

```
o conf plugin_list push CPAN::Plugin::Specfile=dir,/tmp/specfiles-000042
```

The default directory for this is the "plugins/CPAN::Plugin::Specfile" directory in the cpan_home directory.

AUTHOR

Andreas Koenig <andk@cpan.org>, Branislav Zahradnik <barney@cpan.org>

perl v5.34.0

2023-11-23

CPAN::Plugin::Specfile(3perl)