



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Crypt::Digest::Whirlpool.3pm'

\$ man Crypt::Digest::Whirlpool.3pm

Crypt::Digest::Whirlpool(3pm) User Contributed Perl Documentation Crypt::Digest::Whirlpool(3pm)

NAME

Crypt::Digest::Whirlpool - Hash function Whirlpool [size: 512 bits]

SYNOPSIS

Functional interface:

```
use Crypt::Digest::Whirlpool qw( whirlpool whirlpool_hex whirlpool_b64 whirlpool_b64u  
                                whirlpool_file whirlpool_file_hex whirlpool_file_b64 whirlpool_file_b64u );
```

calculate digest from string/buffer

```
$whirlpool_raw = whirlpool('data string');
```

```
$whirlpool_hex = whirlpool_hex('data string');
```

```
$whirlpool_b64 = whirlpool_b64('data string');
```

```
$whirlpool_b64u = whirlpool_b64u('data string');
```

calculate digest from file

```
$whirlpool_raw = whirlpool_file('filename.dat');
```

```
$whirlpool_hex = whirlpool_file_hex('filename.dat');
```

```
$whirlpool_b64 = whirlpool_file_b64('filename.dat');
```

```
$whirlpool_b64u = whirlpool_file_b64u('filename.dat');
```

calculate digest from filehandle

```
$whirlpool_raw = whirlpool_file(*FILEHANDLE);
```

```
$whirlpool_hex = whirlpool_file_hex(*FILEHANDLE);
```

```

$whirlpool_b64 = whirlpool_file_b64(*FILEHANDLE);
$whirlpool_b64u = whirlpool_file_b64u(*FILEHANDLE);

### OO interface:
use Crypt::Digest::Whirlpool;

$d = Crypt::Digest::Whirlpool->new;
$d->add('any data');
$d->addfile('filename.dat');
$d->addfile(*FILEHANDLE);
$result_raw = $d->digest; # raw bytes
$result_hex = $d->hexdigest; # hexadecimal form
$result_b64 = $d->b64digest; # Base64 form
$result_b64u = $d->b64udigest; # Base64 URL Safe form

```

DESCRIPTION

Provides an interface to the Whirlpool digest algorithm.

EXPORT

Nothing is exported by default.

You can export selected functions:

```

use Crypt::Digest::Whirlpool qw(whirlpool whirlpool_hex whirlpool_b64 whirlpool_b64u
                                whirlpool_file whirlpool_file_hex whirlpool_file_b64 whirlpool_file_b64u);

```

Or all of them at once:

```

use Crypt::Digest::Whirlpool ':all';

```

FUNCTIONS

`whirlpool`

Logically joins all arguments into a single string, and returns its Whirlpool digest

encoded as a binary string.

```
$whirlpool_raw = whirlpool('data string');
```

```
#or
```

```
$whirlpool_raw = whirlpool('any data', 'more data', 'even more data');
```

whirlpool_hex

Logically joins all arguments into a single string, and returns its Whirlpool digest encoded as a hexadecimal string.

```
$whirlpool_hex = whirlpool_hex('data string');
```

```
#or
```

```
$whirlpool_hex = whirlpool_hex('any data', 'more data', 'even more data');
```

whirlpool_b64

Logically joins all arguments into a single string, and returns its Whirlpool digest encoded as a Base64 string, with trailing '=' padding.

```
$whirlpool_b64 = whirlpool_b64('data string');
```

```
#or
```

```
$whirlpool_b64 = whirlpool_b64('any data', 'more data', 'even more data');
```

whirlpool_b64u

Logically joins all arguments into a single string, and returns its Whirlpool digest encoded as a Base64 URL Safe string (see RFC 4648 section 5).

```
$whirlpool_b64url = whirlpool_b64u('data string');
```

```
#or
```

```
$whirlpool_b64url = whirlpool_b64u('any data', 'more data', 'even more data');
```

whirlpool_file

Reads file (defined by filename or filehandle) content, and returns its Whirlpool digest encoded as a binary string.

```
$whirlpool_raw = whirlpool_file('filename.dat');
```

```
#or
```

```
$whirlpool_raw = whirlpool_file(*FILEHANDLE);
```

whirlpool_file_hex

Reads file (defined by filename or filehandle) content, and returns its Whirlpool digest encoded as a hexadecimal string.

```
$whirlpool_hex = whirlpool_file_hex('filename.dat');
```

```
#or
```

```
$whirlpool_hex = whirlpool_file_hex(*FILEHANDLE);
```

BEWARE: You have to make sure that the filehandle is in binary mode before you pass it as argument to the addfile() method.

whirlpool_file_b64

Reads file (defined by filename or filehandle) content, and returns its Whirlpool digest encoded as a Base64 string, with trailing '=' padding.

```
$whirlpool_b64 = whirlpool_file_b64('filename.dat');
```

```
#or
```

```
$whirlpool_b64 = whirlpool_file_b64(*FILEHANDLE);
```

whirlpool_file_b64u

Reads file (defined by filename or filehandle) content, and returns its Whirlpool digest encoded as a Base64 URL Safe string (see RFC 4648 section 5).

```
$whirlpool_b64url = whirlpool_file_b64u('filename.dat');
```

```
#or
```

```
$whirlpool_b64url = whirlpool_file_b64u(*FILEHANDLE);
```

The OO interface provides the same set of functions as Crypt::Digest.

new

```
$d = Crypt::Digest::Whirlpool->new();
```

clone

```
$d->clone();
```

reset

```
$d->reset();
```

add

```
$d->add('any data');
```

#or

```
$d->add('any data', 'more data', 'even more data');
```

addfile

```
$d->addfile('filename.dat');
```

#or

```
$d->addfile(*FILEHANDLE);
```

add_bits

```
$d->add_bits($bit_string); # e.g. $d->add_bits("111100001010");
```

#or

```
$d->add_bits($data, $nbits); # e.g. $d->add_bits("\xF0xA0", 16);
```

hashsize

```
$d->hashsize;
```

#or

```
Crypt::Digest::Whirlpool->hashsize();
```

#or

```
Crypt::Digest::Whirlpool::hashsize();
```

digest

```
$result_raw = $d->digest();
```

hexdigest

```
$result_hex = $d->hexdigest();
```

b64digest

```
$result_b64 = $d->b64digest();
```

b64udigest

```
$result_b64url = $d->b64udigest();
```

SEE ALSO

? CryptX, Crypt::Digest

? <[https://en.wikipedia.org/wiki/Whirlpool_\(cryptography\)](https://en.wikipedia.org/wiki/Whirlpool_(cryptography))>

perl v5.34.0

2022-02-06

Crypt::Digest::Whirlpool(3pm)