



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Dpkg::Source::Package.3perl'

\$ man Dpkg::Source::Package.3perl

Dpkg::Source::Package(3perl) libdpkg-perl Dpkg::Source::Package(3perl)

NAME

Dpkg::Source::Package - manipulate Debian source packages

DESCRIPTION

This module provides a class that can manipulate Debian source packages. While it supports both the extraction and the creation of source packages, the only API that is officially supported is the one that supports the extraction of the source package.

FUNCTIONS

`$string = get_default_diff_ignore_regex()`

Returns the default diff ignore regex.

`set_default_diff_ignore_regex($string)`

Set a regex as the new default diff ignore regex.

`@array = get_default_tar_ignore_pattern()`

Returns the default tar ignore pattern, as an array.

METHODS

`$p = Dpkg::Source::Package->new(%opts, options => {})`

Creates a new object corresponding to a source package. When the key filename is set to a .dsc file, it will be used to initialize the source package with its description.

Otherwise if the format key is set to a valid value, the object will be initialized for that format (since dpkg 1.19.3).

The options key is a hash ref which supports the following options:

skip_debianization

If set to 1, do not apply Debian changes on the extracted source package.

skip_patches

If set to 1, do not apply Debian-specific patches. This options is specific for source packages using format "2.0" and "3.0 (quilt)".

require_valid_signature

If set to 1, the check_signature() method will be stricter and will error out if the signature can't be verified.

require_strong_checksums

If set to 1, the check_checksums() method will be stricter and will error out if there is no strong checksum.

copy_orig_tarballs

If set to 1, the extraction will copy the upstream tarballs next the target directory. This is useful if you want to be able to rebuild the source package after its extraction.

`$p->get_filename()`

Returns the filename of the DSC file.

`$p->get_files()`

Returns the list of files referenced by the source package. The filenames usually do not have any path information.

`$p->check_checksums()`

Verify the checksums embedded in the DSC file. It requires the presence of the other files constituting the source package. If any inconsistency is discovered, it immediately errors out. It will make sure at least one strong checksum is present.

If the object has been created with the "require_strong_checksums" option, then any problem will result in a fatal error.

`$p->get_upstream_signing_key($dir)`

Get the filename for the upstream key.

`$p->check_original_tarball_signature($dir, @asc)`

Verify the original upstream tarball signatures @asc using the upstream public keys.

It requires the origin upstream tarballs, their signatures and the upstream signing key, as found in an unpacked source tree \$dir. If any inconsistency is discovered, it immediately errors out.

`$bool = $p->is_signed()`

Returns 1 if the DSC files contains an embedded OpenPGP signature. Otherwise returns

0.

`$p->check_signature()`

Implement the same OpenPGP signature check that `dpkg-source` does. In case of problems, it prints a warning or errors out.

If the object has been created with the "require_valid_signature" option, then any problem will result in a fatal error.

`$p->extract($targetdir)`

Extracts the source package in the target directory `$targetdir`. Beware that if `$targetdir` already exists, it will be erased (as long as the `no_overwrite_dir` option is set).

CHANGES

Version 2.01 (dpkg 1.20.1)

New method: `get_upstream_signing_key()`.

Version 2.00 (dpkg 1.20.0)

New method: `check_original_tarball_signature()`.

Remove variable: `$diff_ignore_default_regexp`.

Hide variable: `@tar_ignore_default_pattern`.

Version 1.03 (dpkg 1.19.3)

New option: `format` in `new()`.

Version 1.02 (dpkg 1.18.7)

New option: `require_strong_checksums` in `check_checksums()`.

Version 1.01 (dpkg 1.17.2)

New functions: `get_default_diff_ignore_regex()`, `set_default_diff_ignore_regex()`,
`get_default_tar_ignore_pattern()`

Deprecated variables: `$diff_ignore_default_regexp`, `@tar_ignore_default_pattern`

Version 1.00 (dpkg 1.16.1)

Mark the module as public.

1.21.1

2024-02-23

Dpkg::Source::Package(3perl)