



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Dpkg::Vendor.3perl'

\$ man Dpkg::Vendor.3perl

Dpkg::Vendor(3perl) libdpkg-perl Dpkg::Vendor(3perl)

NAME

Dpkg::Vendor - get access to some vendor specific information

DESCRIPTION

The files in \$Dpkg::CONFDIR/origins/ can provide information about various vendors who are providing Debian packages. Currently those files look like this:

Vendor: Debian

Vendor-URL: <https://www.debian.org/>

Bugs: [debbugs://bugs.debian.org](https://bugs.debian.org/)

If the vendor derives from another vendor, the file should document the relationship by listing the base distribution in the Parent field:

Parent: Debian

The file should be named according to the vendor name. The usual convention is to name the vendor file using the vendor name in all lowercase, but some variation is permitted.

Namely, spaces are mapped to dashes ('-'), and the file can have the same casing as the Vendor field, or it can be capitalized.

FUNCTIONS

`$dir = get_vendor_dir()`

Returns the current dpkg origins directory name, where the vendor files are stored.

`$fields = get_vendor_info($name)`

Returns a `Dpkg::Control` object with the information parsed from the corresponding vendor file in `$Dpkg::CONFDIR/origins/`. If `$name` is omitted, it will use `$Dpkg::CONFDIR/origins/default` which is supposed to be a symlink to the vendor of the currently installed operating system. Returns `undef` if there's no file for the given vendor.

`$name = get_vendor_file($name)`

Check if there's a file for the given vendor and returns its name.

`$name = get_current_vendor()`

Returns the name of the current vendor. If `DEB_VENDOR` is set, it uses that first, otherwise it falls back to parsing `$Dpkg::CONFDIR/origins/default`. If that file doesn't exist, it returns `undef`.

`$object = get_vendor_object($name)`

Return the `Dpkg::Vendor::*` object of the corresponding vendor. If `$name` is omitted, return the object of the current vendor. If no vendor can be identified, then return the `Dpkg::Vendor::Default` object.

`run_vendor_hook($hookid, @params)`

Run a hook implemented by the current vendor object.

CHANGES

Version 1.01 (dpkg 1.17.0)

New function: `get_vendor_dir()`.

Version 1.00 (dpkg 1.16.1)

Mark the module as public.

SEE ALSO

deb-origin(5).

1.21.1

2024-02-23

Dpkg::Vendor(3perl)