



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'EVP_PKEY-DSA.7ssl'

\$ man EVP_PKEY-DSA.7ssl

EVP_PKEY-DSA(7SSL) OpenSSL EVP_PKEY-DSA(7SSL)

NAME

EVP_PKEY-DSA, EVP_KEYMGMT-DSA - EVP_PKEY DSA keytype and algorithm support

DESCRIPTION

For DSA the FIPS186-4 standard specifies that the values used for FFC parameter generation are also required for parameter validation. This means that optional FFC domain parameter values for seed, pcounter and gindex may need to be stored for validation purposes. For DSA these fields are not stored in the ASN1 data so they need to be stored externally if validation is required.

DSA parameters

The DSA key type supports the FFC parameters (see "FFC parameters" in EVP_PKEY-FFC(7)).

DSA key generation parameters

The DSA key type supports the FFC key generation parameters (see "FFC key generation parameters" in EVP_PKEY-FFC(7))

The following restrictions apply to the "pbits" field:

For "fips186_4" this must be either 2048 or 3072. For "fips186_2" this must be 1024. For "group" this can be any one of 2048, 3072, 4096, 6144 or 8192.

EXAMPLES

An EVP_PKEY context can be obtained by calling:

```
EVP_PKEY_CTX *pctx = EVP_PKEY_CTX_new_from_name(NULL, "DSA", NULL);
```

The DSA domain parameters can be generated by calling:

```
unsigned int pbits = 2048;
unsigned int qbits = 256;
int gindex = 1;
OSSL_PARAM params[5];
EVP_PKEY *param_key = NULL;
EVP_PKEY_CTX *pctx = NULL;

pctx = EVP_PKEY_CTX_new_from_name(NULL, "DSA", NULL);
EVP_PKEY_paramgen_init(pctx);

params[0] = OSSL_PARAM_construct_uint("pbits", &pbits);
params[1] = OSSL_PARAM_construct_uint("qbits", &qbits);
params[2] = OSSL_PARAM_construct_int("gindex", &gindex);
params[3] = OSSL_PARAM_construct_utf8_string("digest", "SHA384", 0);
params[4] = OSSL_PARAM_construct_end();
EVP_PKEY_CTX_set_params(pctx, params);

EVP_PKEY_generate(pctx, &param_key);
EVP_PKEY_CTX_free(pctx);

EVP_PKEY_print_params(bio_out, param_key, 0, NULL);
```

A DSA key can be generated using domain parameters by calling:

```
EVP_PKEY *key = NULL;
```

```
EVP_PKEY_CTX *gctx = NULL;
```

```
gctx = EVP_PKEY_CTX_new_from_pkey(NULL, param_key, NULL);
```

```
EVP_PKEY_keygen_init(gctx);
```

```
EVP_PKEY_generate(gctx, &key);
```

```
EVP_PKEY_CTX_free(gctx);
```

```
EVP_PKEY_print_private(bio_out, key, 0, NULL);
```

CONFORMING TO

The following sections of FIPS 186-4:

A.1.1.2 Generation of Probable Primes p and q Using an Approved Hash Function.

A.2.3 Generation of canonical generator g .

A.2.1 Unverifiable Generation of the Generator g .

SEE ALSO

EVP_PKEY-FFC(7), EVP_SIGNATURE-DSA(7) EVP_PKEY(3), provider-keymgmt(7), EVP_KEYMGMT(3),
OSSL_PROVIDER-default(7), OSSL_PROVIDER-FIPS(7)

COPYRIGHT

Copyright 2020-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.2

2024-02-16

EVP_PKEY-DSA(7SSL)