



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'ExtUtils::MM\_Cygwin.3perl'***

***\$ man ExtUtils::MM\_Cygwin.3perl***

ExtUtils::MM\_Cygwin(3perl) Perl Programmers Reference Guide ExtUtils::MM\_Cygwin(3perl)

NAME

ExtUtils::MM\_Cygwin - methods to override UN\*X behaviour in ExtUtils::MakeMaker

SYNOPSIS

use ExtUtils::MM\_Cygwin; # Done internally by ExtUtils::MakeMaker if needed

DESCRIPTION

See ExtUtils::MM\_Unix for a documentation of the methods provided there.

os\_flavor

We're Unix and Cygwin.

cflags

if configured for dynamic loading, triggers #define EXT in EXTERN.h

replace\_manpage\_separator

replaces strings ':' with '.' in MAN\*POD man page names

init\_linker

points to libperl.a

maybe\_command

Determine whether a file is native to Cygwin by checking whether it resides inside the Cygwin installation (using Windows paths). If so, use ExtUtils::MM\_Unix to determine if it may be a command. Otherwise use the tests from ExtUtils::MM\_Win32.

dynamic\_lib

Use the default to produce the \*.dll's. But for new archdir dll's use the same rebase address if the old exists.

install

Rebase dll's with the global rebase database after installation.

perl v5.34.0

2023-11-23

ExtUtils::MM\_Cygwin(3perl)