



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'ExtUtils::MM_VMS.3perl'

\$ man ExtUtils::MM_VMS.3perl

ExtUtils::MM_VMS(3perl) Perl Programmers Reference Guide ExtUtils::MM_VMS(3perl)

NAME

ExtUtils::MM_VMS - methods to override UN*X behaviour in ExtUtils::MakeMaker

SYNOPSIS

Do not use this directly.

Instead, use ExtUtils::MM and it will figure out which MM_* class to use for you.

DESCRIPTION

See ExtUtils::MM_Unix for a documentation of the methods provided there. This package overrides the implementation of these methods, not the semantics.

Methods always loaded

wraplist

Converts a list into a string wrapped at approximately 80 columns.

Methods

Those methods which override default MM_Unix methods are marked "(override)", while methods unique to MM_VMS are marked "(specific)". For overridden methods, documentation is limited to an explanation of why this method overrides the MM_Unix method; see the ExtUtils::MM_Unix documentation for more details.

guess_name (override)

Try to determine name of extension being built. We begin with the name of the current directory. Since VMS filenames are case-insensitive, however, we look for a .pm file whose name matches that of the current directory (presumably the 'main' .pm file for this extension), and try to find a "package" statement from which to obtain the

Mixed::Case package name.

find_perl (override)

Use VMS file specification syntax and CLI commands to find and invoke Perl images.

_fixin_replace_shebang (override)

Helper routine for MM->fixin(), overridden because there's no such thing as an actual shebang line that will be interpreted by the shell, so we just prepend \$Config{startperl} and preserve the shebang line argument for any switches it may contain.

maybe_command (override)

Follows VMS naming conventions for executable files. If the name passed in doesn't exactly match an executable file, appends .Exe (or equivalent) to check for executable image, and .Com to check for DCL procedure. If this fails, checks directories in DCL\$PATH and finally Sys\$System: for an executable file having the name specified, with or without the .Exe-equivalent suffix.

pasthru (override)

The list of macro definitions to be passed through must be specified using the /MACRO qualifier and must not add another /DEFINE qualifier. We prepend our own comma here to the contents of \$(PASTHRU_DEFINE) because it is often empty and a comma always present in CCFLAGS would generate a missing qualifier value error.

pm_to_blib (override)

VMS wants a dot in every file so we can't have one called 'pm_to_blib', it becomes 'pm_to_blib.' and MMS/K isn't smart enough to know that when you have a target called 'pm_to_blib' it should look for 'pm_to_blib.'.

So in VMS its pm_to_blib.ts.

perl_script (override)

If name passed in doesn't specify a readable file, appends .com or .pl and tries again, since it's customary to have file types on all files under VMS.

replace_manpage_separator

Use as separator a character which is legal in a VMS-syntax file name.

init_DEST

(override) Because of the difficulty concatenating VMS filepaths we must pre-expand the DEST* variables.

init_DIRFILESEP

No separator between a directory path and a filename on VMS.

init_main (override)

init_tools (override)

Provide VMS-specific forms of various utility commands.

Sets DEV_NULL to nothing because I don't know how to do it on VMS.

Changes EQUALIZE_TIMESTAMP to set revision date of target file to one second later than source file, since MMK interprets precisely equal revision dates for a source and target file as a sign that the target needs to be updated.

init_platform (override)

Add PERL_VMS, MM_VMS_REVISION and MM_VMS_VERSION.

MM_VMS_REVISION is for backwards compatibility before MM_VMS had a \$VERSION.

platform_constants

init_VERSION (override)

Override the *DEFINE_VERSION macros with VMS semantics. Translate the MAKEMAKER filepath to VMS style.

constants (override)

Fixes up numerous file and directory macros to insure VMS syntax regardless of input syntax. Also makes lists of files comma-separated.

special_targets

Clear the default .SUFFIXES and put in our own list.

cflags (override)

Bypass shell script and produce qualifiers for CC directly (but warn user if a shell script for this extension exists). Fold multiple /Defines into one, since some C compilers pay attention to only one instance of this qualifier on the command line.

const_cccmd (override)

Adds directives to point C preprocessor to the right place when handling #include <sys/foo.h> directives. Also constructs CC command line a bit differently than MM_Unix method.

tools_other (override)

Throw in some dubious extra macros for Makefile args.

Also keep around the old \$(SAY) macro in case somebody's using it.

init_dist (override)

VMSish defaults for some values.

macro	description	default
ZIPFLAGS	flags to pass to ZIP	-Vu
COMPRESS	compression command to use for tarfiles	gzip
SUFFIX	suffix to put on compressed files	-gz
SHAR	shar command to use	vms_share
DIST_DEFAULT	default target to use to create a distribution	tardist
DISTVNAME	Use VERSION_SYM instead of VERSION for the name	\$(DISTNAME)-\$(VERSION_SYM)

c_o (override)

Use VMS syntax on command line. In particular, \$(DEFINE) and \$(PERL_INC) have been pulled into \$(CCCMD). Also use MM[SK] macros.

xs_c (override)

Use MM[SK] macros.

xs_o (override)

Use MM[SK] macros, and VMS command line for C compiler.

_xsbuild_replace_macro (override)

There is no simple replacement possible since a qualifier and all its subqualifiers must be considered together, so we use our own utility routine for the replacement.

_xsbuild_value (override)

Convert the extension spec to Unix format, as that's what will match what's in the XSBUILD data structure.

dlsyms (override)

Create VMS linker options files specifying universal symbols for this extension's shareable image(s), and listing other shareable images or libraries to which it should be linked.

xs_obj_opt

Override to fixup -o flags.

dynamic_lib (override)

Use VMS Link command.

xs_make_static_lib (override)

Use VMS commands to manipulate object library.

static_lib_pure_cmd (override)

Use VMS commands to manipulate object library.

xs_static_lib_is_xs

extra_clean_files

Clean up some OS specific files. Plus the temp file used to shorten a lot of commands. And the name mangler database.

zipfile_target

tarfile_target

shdist_target

Syntax for invoking shar, tar and zip differs from that for Unix.

install (override)

Work around DCL's 255 character limit several times, and use VMS-style command line quoting in a few cases.

perldepend (override)

Use VMS-style syntax for files; it's cheaper to just do it directly here than to have the MM_Unix method call "catfile" repeatedly. Also, if we have to rebuild Config.pm, use MM[SK] to do it.

makeaperl (override)

Undertake to build a new set of Perl images using VMS commands. Since VMS does dynamic loading, it's not necessary to statically link each extension into the Perl image, so this isn't the normal build path. Consequently, it hasn't really been tested, and may well be incomplete.

maketext_filter (override)

Ensure that colons marking targets are preceded by space, in order to distinguish the target delimiter from a colon appearing as part of a filespec.

prefixify (override)

prefixifying on VMS is simple. Each should simply be:

```
perl_root:[some.dir]
```

which can just be converted to:

```
volume:[your.prefix.some.dir]
```

otherwise you get the default layout.

In effect, your search prefix is ignored and \$Config{vms_prefix} is used instead.

cd

oneliner

echo

perl trips up on "<foo>" thinking it's an input redirect. So we use the native Write command instead. Besides, it's faster.

quote_literal

escape_dollarsigns

Quote, don't escape.

escape_all_dollarsigns

Quote, don't escape.

escape_newlines

max_exec_len

256 characters.

init_linker

catdir (override)

catfile (override)

Eliminate the macros in the output to the MMS/MMK file.

(File::Spec::VMS used to do this for us, but it's being removed)

eliminate_macros

Expands MM[KS]/Make macros in a text string, using the contents of identically named elements of %\$self, and returns the result as a file specification in Unix syntax.

NOTE: This is the canonical version of the method. The version in File::Spec::VMS is deprecated.

fixpath

```
my $path = $mm->fixpath($path);
```

```
my $path = $mm->fixpath($path, $is_dir);
```

Catchall routine to clean up problem MM[SK]/Make macros. Expands macros in any directory specification, in order to avoid juxtaposing two VMS-syntax directories when MM[SK] is run. Also expands expressions which are all macro, so that we can tell how long the expansion is, and avoid overrunning DCL's command buffer when MM[KS] is running.

fixpath() checks to see whether the result matches the name of a directory in the current default directory and returns a directory or file specification accordingly.

`$is_dir` can be set to true to force `fixpath()` to consider the path to be a directory or false to force it to be a file.

NOTE: This is the canonical version of the method. The version in `File::Spec::VMS` is deprecated.

`os_flavor`

VMS is VMS.

`is_make_type` (override)

None of the make types being checked for is viable on VMS, plus our `$self->{MAKE}` is an unexpanded (and unexpandable) macro whose value is known only to the make utility itself.

`make_type` (override)

Returns a suitable string describing the type of makefile being written.

AUTHOR

Original author Charles Bailey bailey@newman.upenn.edu

Maintained by Michael G Schwern schwern@pobox.com

See `ExtUtils::MakeMaker` for patching and contact information.

perl v5.34.0

2023-11-23

ExtUtils::MM_VMS(3perl)