



## ***Linux Ubuntu 22.4.5 Manual Pages on command 'Font::TTF::AATutils.3pm'***

***\$ man Font::TTF::AATutils.3pm***

Font::TTF::AATutils(3pm) User Contributed Perl Documentation Font::TTF::AATutils(3pm)

### NAME

Font::TTF::AATutils - Utility functions for AAT tables

```
($classes, $states) = AAT_read_subtable($fh, $baseOffset, $subtableStart, $limits)
```

```
$length = AAT_write_state_table($fh, $classes, $states, $numExtraTables, $packEntry)
```

\$packEntry is a subroutine for packing an entry into binary form, called as

```
$dat = $packEntry($entry, $entryTable, $numEntries)
```

where the entry is a comma-separated list of nextStateOffset, flags, actions

```
($classes, $states, $entries) = AAT_read_state_table($fh, $numActionWords)
```

```
($format, $lookup) = AAT_read_lookup($fh, $valueSize, $length, $default)
```

```
AAT_write_lookup($fh, $format, $lookup, $valueSize, $default)
```

### AUTHOR

Jonathan Kew <<http://scripts.sil.org/FontUtils>>.

### LICENSING

Copyright (c) 1998-2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details,  
see the full text of the license in the file LICENSE.

perl v5.24.1

2016-08-28

Font::TTF::AATutils(3pm)