



Linux Ubuntu 22.4.5 Manual Pages on command 'Font::TTF::PCLT.3pm'

\$ man Font::TTF::PCLT.3pm

Font::TTF::PCLT(3pm) User Contributed Perl Documentation Font::TTF::PCLT(3pm)

NAME

Font::TTF::PCLT - PCLT TrueType font table

DESCRIPTION

The PCLT table holds various pieces HP-PCL specific information. Information here is generally not used by other software, except for the xHeight and CapHeight which are stored here (if the table exists in a font).

INSTANCE VARIABLES

Only from table and the standard:

version

FontNumber

Pitch

xHeight

Style

TypeFamily

CapHeight

SymbolSet

Typeface

CharacterComplement

FileName

StrokeWeight

WidthType

SerifStyle

Notice that "Typeface", "CharacterComplement" and "FileName" return arrays of unsigned characters of the appropriate length

METHODS

`$t->read`

Reads the table into memory thanks to some utility functions

`$t->out($fh)`

Writes the table to a file either from memory or by copying.

`$t->minsize()`

Returns the minimum size this table can be. If it is smaller than this, then the table must be bad and should be deleted or whatever.

BUGS

None known

AUTHOR

Martin Hosken <<http://scripts.sil.org/FontUtils>>.

LICENSING

Copyright (c) 1998-2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details, see the full text of the license in the file LICENSE.