



Linux Ubuntu 22.4.5 Manual Pages on command 'Font::TTF::Post.3pm'

\$ man Font::TTF::Post.3pm

Font::TTF::Post(3pm) User Contributed Perl Documentation Font::TTF::Post(3pm)

NAME

Font::TTF::Post - Holds the Postscript names for each glyph

DESCRIPTION

Holds the postscript names for glyphs. Note that they are not held as an array, but as indexes into two lists. The first list is the standard Postscript name list defined by the TrueType standard. The second comes from the font directly.

Looking up a glyph from a Postscript name or a name from a glyph number is achieved through methods rather than variable lookup.

This class handles PostScript table types of 1, 2, 2.5 & 3, but not version 4.

Support for version 2.5 is as per Apple spec rather than MS.

The way to look up Postscript names or glyphs is:

```
$pname = $f->{'post'}{'VAL'}[$gnum];  
$gnum = $f->{'post'}{'STRINGS'}{$pname};
```

INSTANCE VARIABLES

Due to different systems having different limitations, there are various class variables available to control what post table types can be written.

`$Font::TTF::Post::no25`

If set tells `Font::TTF::Post::out` to use table type 2 instead of 2.5 in case apps cannot handle version 2.5.

`VAL` Contains an array indexed by glyph number of Postscript names. This is used when writing out a font.

STRINGS

An associative array of Postscript names mapping to the highest glyph with that name. These may not be in sync with `VAL`.

In addition there are the standard introductory variables defined in the standard:

`FormatType`

`italicAngle`

`underlinePosition`

`underlineThickness`

`isFixedPitch`

`minMemType42`

`maxMemType42`

`minMemType1`

`maxMemType1`

METHODS

`$t->read`

Reads the Postscript table into memory from disk

`$t->out($fh)`

Writes out a new Postscript name table from memory or copies from disk

`$t->XML_element($context, $depth, $key, $val)`

Outputs the names as one block of XML

`$t->minsize()`

Returns the minimum size this table can be. If it is smaller than this, then the table must be bad and should be deleted or whatever.

BUGS

? No support for type 4 tables

AUTHOR

Martin Hosken <<http://scripts.sil.org/FontUtils>>.

LICENSING

Copyright (c) 1998-2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details, see the full text of the license in the file LICENSE.

perl v5.24.1

2016-08-28

Font::TTF::Post(3pm)