



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Opcode.3perl'

\$ man Opcode.3perl

Opcode(3perl) Perl Programmers Reference Guide Opcode(3perl)

NAME

Opcode - Disable named opcodes when compiling perl code

SYNOPSIS

use Opcode;

DESCRIPTION

Perl code is always compiled into an internal format before execution.

Evaluating perl code (e.g. via "eval" or "do 'file'") causes the code to be compiled into an internal format and then, provided there was no error in the compilation, executed.

The internal format is based on many distinct opcodes.

By default no opmask is in effect and any code can be compiled.

The Opcode module allow you to define an operator mask to be in effect when perl next compiles any code. Attempting to compile code which contains a masked opcode will cause the compilation to fail with an error. The code will not be executed.

NOTE

The Opcode module is not usually used directly. See the ops pragma and Safe modules for more typical uses.

WARNING

The Opcode module does not implement an effective sandbox for evaluating untrusted code with the perl interpreter.

Bugs in the perl interpreter that could be abused to bypass Opcode restrictions are not treated as vulnerabilities. See perlsecpolicy for additional information.

The authors make no warranty, implied or otherwise, about the suitability of this software

for safety or security purposes.

The authors shall not in any case be liable for special, incidental, consequential, indirect or other similar damages arising from the use of this software.

Your mileage will vary. If in any doubt do not use it.

Operator Names and Operator Lists

The canonical list of operator names is the contents of the array `PL_op_name` defined and initialised in file `opcode.h` of the Perl source distribution (and installed into the perl library).

Each operator has both a terse name (its `opname`) and a more verbose or recognisable descriptive name. The `opdesc` function can be used to return a list of descriptions for a list of operators.

Many of the functions and methods listed below take a list of operators as parameters.

Most operator lists can be made up of several types of element. Each element can be one of an operator name (`opname`)

- Operator names are typically small lowercase words like `enterloop`, `leaveloop`, `last`, `next`, `redo` etc. Sometimes they are rather cryptic like `gv2cv`, `i_ncmp` and `ftsvtx`.

an operator tag name (`optag`)

- Operator tags can be used to refer to groups (or sets) of operators. Tag names always begin with a colon. The `Opcode` module defines several `optags` and the user can define others using the `define_optag` function.

a negated `opname` or `optag`

- An `opname` or `optag` can be prefixed with an exclamation mark, e.g., `!mkdir`.

- Negating an `opname` or `optag` means remove the corresponding ops from the accumulated set of ops at that point.

an operator set (`opset`)

- An `opset` as a binary string of approximately 44 bytes which holds a set or zero or more operators.

- The `opset` and `opset_to_ops` functions can be used to convert from a list of operators to an `opset` and vice versa.

- Wherever a list of operators can be given you can use one or more `opsets`. See also `Manipulating Opsets` below.

The Opcode package contains functions for manipulating operator names tags and sets. All are available for export by the package.

`opcodes` In a scalar context `opcodes` returns the number of opcodes in this version of perl (around 350 for perl-5.7.0).

In a list context it returns a list of all the operator names. (Not yet implemented, use `@names = opset_to_ops(full_opset)`.)

`opset (OP, ...)`

Returns an opset containing the listed operators.

`opset_to_ops (OPSET)`

Returns a list of operator names corresponding to those operators in the set.

`opset_to_hex (OPSET)`

Returns a string representation of an opset. Can be handy for debugging.

`full_opset`

Returns an opset which includes all operators.

`empty_opset`

Returns an opset which contains no operators.

`invert_opset (OPSET)`

Returns an opset which is the inverse set of the one supplied.

`verify_opset (OPSET, ...)`

Returns true if the supplied opset looks like a valid opset (is the right length etc) otherwise it returns false. If an optional second parameter is true then `verify_opset` will croak on an invalid opset instead of returning false.

Most of the other Opcode functions call `verify_opset` automatically and will croak if given an invalid opset.

`define_optag (OPTAG, OPSET)`

Define OPTAG as a symbolic name for OPSET. Optag names always start with a colon ":".

The optag name used must not be defined already (`define_optag` will croak if it is already defined). Optag names are global to the perl process and optag definitions cannot be altered or deleted once defined.

It is strongly recommended that applications using Opcode should use a leading capital letter on their tag names since lowercase names are reserved for use by the Opcode module. If using Opcode within a module you should prefix your tags

names with the name of your module to ensure uniqueness and thus avoid clashes with other modules.

opmask_add (OPSET)

Adds the supplied opset to the current opmask. Note that there is currently no mechanism for unmasking ops once they have been masked. This is intentional.

opmask Returns an opset corresponding to the current opmask.

opdesc (OP, ...)

This takes a list of operator names and returns the corresponding list of operator descriptions.

opdump (PAT)

Dumps to STDOUT a two column list of op names and op descriptions. If an optional pattern is given then only lines which match the (case insensitive) pattern will be output.

It's designed to be used as a handy command line utility:

```
perl -MOpcode=opdump -e opdump
```

```
perl -MOpcode=opdump -e 'opdump Eval'
```

Manipulating Opsets

Opsets may be manipulated using the perl bit vector operators & (and), | (or), ^ (xor) and ~ (negate/invert).

However you should never rely on the numerical position of any opcode within the opset. In other words both sides of a bit vector operator should be opsets returned from Opcode functions.

Also, since the number of opcodes in your current version of perl might not be an exact multiple of eight, there may be unused bits in the last byte of an upset. This should not cause any problems (Opcode functions ignore those extra bits) but it does mean that using the ~ operator will typically not produce the same 'physical' opset 'string' as the invert_opset function.

TO DO (maybe)

```
$bool = opset_eq($opset1, $opset2) true if opsets are logically  
equivalent
```

```
$yes = opset_can($opset, @ops) true if $opset has all @ops set
```

```
@diff = opset_diff($opset1, $opset2) => ('foo', '!bar', ...)
```

:base_core

null stub scalar pushmark wantarray const defined undef
rv2sv sassign
rv2av aassign aelem aelemfast aelemfast_lex aslice kvaslice
av2arylen
rv2hv helem hslice kvhslice each values keys exists delete
aeach akeys avalues multideref argelem argdefelem argcheck
preinc i_preinc predec i_predec postinc i_postinc
postdec i_postdec int hex oct abs pow multiply i_multiply
divide i_divide modulo i_modulo add i_add subtract i_subtract
left_shift right_shift bit_and bit_xor bit_or nbit_and
nbit_xor nbit_or sbit_and sbit_xor sbit_or negate i_negate not
complement ncomplement scomplement
lt i_lt gt i_gt le i_le ge i_ge eq i_eq ne i_nencmp i_ncmp
slt sgt sle sge seq sne scmp
isa
substr vec stringify study pos length index rindex ord chr
ucfirst lcfirst uc lc fc quotemeta trans transr chop schop
chomp schomp
match split qr
list lslice splice push pop shift unshift reverse
cond_expr flip flop andassign orassign dorassign and or dor xor
warn die lineseq nextstate scope enter leave
rv2cv anoncode prototype coreargs avhvswitch anonconst
entersub leavesub leavesublv return method method_named
method_super method_redir method_redir_super
-- XXX loops via recursion?
cmpchain_and cmpchain_dup
leaveeval -- needed for Safe to operate, is safe
without entereval

:base_mem

These memory related ops are not included in :base_core because they can easily be used to implement a resource attack (e.g., consume all available memory).

concat multiconcat repeat join range

anonlist anonhash

Note that despite the existence of this optag a memory resource attack may still be possible using only :base_core ops.

Disabling these ops is a very heavy handed way to attempt to prevent a memory resource attack. It's probable that a specific memory limit mechanism will be added to perl in the near future.

:base_loop

These loop ops are not included in :base_core because they can easily be used to implement a resource attack (e.g., consume all available CPU time).

grepstart grepwhile

mapstart mapwhile

enteriter iter

enterloop leaveloop unstack

last next redo

goto

:base_io

These ops enable filehandle (rather than filename) based input and output. These are safe on the assumption that only pre-existing filehandles are available for use.

Usually, to create new filehandles other ops such as open would need to be enabled, if you don't take into account the magical open of ARGV.

readline rcatline getc read

formline enterwrite leavewrite

print say sysread syswrite send recv

eof tell seek sysseek

readdir telldir seekdir rewinddir

:base_orig

These are a hotchpotch of opcodes still waiting to be considered

gvsv gv gelem

padsv padav padhv padcv padany padrange introcv clonecv

once

rv2gv refgen srefgen ref refassign lvref lvrefslice lvavref

bless -- could be used to change ownership of objects

(re blessing)

regcmaybe regcreset regcomp subst substcont

sprintf prtf -- can core dump

crypt

tie untie

dbmopen dbmclose

sselect select

pipe_op sockpair

getppid getpgrp setpgrp getpriority setpriority

localtime gmtime

entertry leavetry -- can be used to 'hide' fatal errors

entertrycatch poptry catch leavetrycatch -- similar

entergiven leavgiven

enterwhen leavewhen

break continue

smartmatch

custom -- where should this go

:base_math

These ops are not included in :base_core because of the risk of them being used to generate floating point exceptions (which would have to be caught using a \$SIG{FPE} handler).

atan2 sin cos exp log sqrt

These ops are not included in :base_core because they have an effect beyond the scope of the compartment.

rand srand

:base_thread

These ops are related to multi-threading.

lock

:default

A handy tag name for a reasonable default set of ops. (The current ops allowed are unstable while development continues. It will change.)

:base_core :base_mem :base_loop :base_orig :base_thread

This list used to contain :base_io prior to Opcode 1.07.

If safety matters to you (and why else would you be using the Opcode module?) then you should not rely on the definition of this, or indeed any other, optag!

:filesystem_read

stat lstat readlink
fstatime fblk fchr fctime fdir fteexec fteowned
fread ftewrite ffile ftis flink fmtime ftpipe
ftreexec ftrowned ftrread ftsuid ftsize ftsock ftsuid
fitty ftzero ftrwrite ftsvtx
fittxt ftbinary
fileno

:sys_db

ghbyname ghbyaddr ghostent shostent ehostent -- hosts
gnbyname gnbyaddr gnetent snentent enentent -- networks
gpbyname gpbynumber gprotoent sprotoent eprotoent -- protocols
gsbyname gsbyport gserver sserver eserver -- services
gpwnam gpwuid gpwent spwent epwent getlogin -- users
ggrnam ggrgid ggreent sgreent egrent -- groups

:browse

A handy tag name for a reasonable default set of ops beyond the :default optag. Like :default (and indeed all the other optags) its current definition is unstable while development continues. It will change.

The :browse tag represents the next step beyond :default. It is a superset of the :default ops and adds :filesystem_read the :sys_db. The intent being that scripts can access more (possibly sensitive) information about your system but not be able to change it.

:default :filesystem_read :sys_db

:filesystem_open

sysopen open close
umask binmode
open_dir closedir -- other dir ops are in :base_io

:filesystem_write

link unlink rename symlink truncate
mkdir rmdir

utime chmod chown

fcntl -- not strictly filesystem related, but possibly as
dangerous?

:subprocess

backtick system

fork

wait waitpid

glob -- access to Cshell via <`rm *`>

:ownprocess

exec exit kill

time tms -- could be used for timing attacks (paranoid?)

:others

This tag holds groups of assorted specialist opcodes that don't warrant having optags defined for them.

SystemV Interprocess Communications:

msgctl msgget msgrcv msgsnd

semctl semget semop

shmctl shmget shmread shmwrite

:load

This tag holds opcodes related to loading modules and getting information about calling environment and args.

require dofile

caller runcv

:still_to_be_decided

chdir

flock ioctl

socket getpeername ssocketopt

bind connect listen accept shutdown gsocketopt getsockname

sleep alarm -- changes global timer state and signal handling

sort -- assorted problems including core dumps

tied -- can be used to access object implementing a tie

pack unpack -- can be used to create/use memory pointers

hintseval -- constant op holding eval hints

entereval -- can be used to hide code from initial compile

reset

dbstate -- perl -d version of nextstate(ment) opcode

:dangerous

This tag is simply a bucket for opcodes that are unlikely to be used via a tag name

but need to be tagged for completeness and documentation.

syscall dump chroot

SEE ALSO

ops -- perl pragma interface to Opcode module.

Safe -- Opcode and namespace limited execution compartments

AUTHORS

Originally designed and implemented by Malcolm Beattie, mbeattie@sable.ox.ac.uk as part of

Safe version 1.

Split out from Safe module version 1, named opcode tags and other changes added by Tim

Bunce.

perl v5.34.0

2023-11-23

Opcode(3perl)