



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Pod::Simple::PullParserToken.3perl'

\$ man Pod::Simple::PullParserToken.3perl

Pod::Simple::PullParserToken(3perl Programmers Reference Guide Pod::Simple::PullParserToken(3perl)

NAME

Pod::Simple::PullParserToken -- tokens from Pod::Simple::PullParser

SYNOPSIS

Given a \$parser that's an object of class Pod::Simple::PullParser (or a subclass)...

```
while(my $token = $parser->get_token) {  
    $DEBUG and print STDERR "Token: ", $token->dump, "\n";  
    if($token->is_start) {  
        ...access $token->tagname, $token->attr, etc...  
    } elsif($token->is_text) {  
        ...access $token->text, $token->text_r, etc...  
    } elsif($token->is_end) {  
        ...access $token->tagname...  
    }  
}
```

(Also see Pod::Simple::PullParser)

DESCRIPTION

When you do \$parser->get_token on a Pod::Simple::PullParser, you should get an object of a subclass of Pod::Simple::PullParserToken.

Subclasses will add methods, and will also inherit these methods:

\$token->type

This returns the type of the token. This will be either the string "start", the string "text", or the string "end".

Once you know what the type of an object is, you then know what subclass it belongs to, and therefore what methods it supports.

Yes, you could probably do the same thing with code like

`$token->isa('Pod::Simple::PullParserEndToken')`, but that's not so pretty as using just

`$token->type`, or even the following shortcuts:

`$token->is_start`

This is a shortcut for `"$token->type() eq "start"`

`$token->is_text`

This is a shortcut for `"$token->type() eq "text"`

`$token->is_end`

This is a shortcut for `"$token->type() eq "end"`

`$token->dump`

This returns a handy stringified value of this object. This is useful for debugging,

as in:

```
while(my $token = $parser->get_token) {  
    $DEBUG and print STDERR "Token: ", $token->dump, "\n";  
    ...  
}
```

SEE ALSO

My subclasses: `Pod::Simple::PullParserStartToken`, `Pod::Simple::PullParserTextToken`, and `Pod::Simple::PullParserEndToken`.

`Pod::Simple::PullParser` and `Pod::Simple`

SUPPORT

Questions or discussion about POD and `Pod::Simple` should be sent to the `pod-people@perl.org` mail list. Send an empty email to `pod-people-subscribe@perl.org` to subscribe.

This module is managed in an open GitHub repository,

<https://github.com/perl-pod/pod-simple/>. Feel free to fork and contribute, or to clone <https://github.com/perl-pod/pod-simple.git> and send patches!

Patches against `Pod::Simple` are welcome. Please send bug reports to

bug-pod-simple@rt.cpan.org.

COPYRIGHT AND DISCLAIMERS

Copyright (c) 2002 Sean M. Burke.

This library is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

This program is distributed in the hope that it will be useful, but without any warranty; without even the implied warranty of merchantability or fitness for a particular purpose.

AUTHOR

Pod::Simple was created by Sean M. Burke <sburke@cpan.org>. But don't bother him, he's retired.

Pod::Simple is maintained by:

? Allison Randal "allison@perl.org"

? Hans Dieter Pearcey "hdp@cpan.org"

? David E. Wheeler "dwheeler@cpan.org"

perl v5.34.0

2023-11-23

Pod::Simple::PullParserToken(3perl)