



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'Test2::EventFacet::Hub.3perl'***

***\$ man Test2::EventFacet::Hub.3perl***

Test2::EventFacet::Hub(3perl) Perl Programmers Reference Guide Test2::EventFacet::Hub(3perl)

NAME

Test2::EventFacet::Hub - Facet for the hubs an event passes through.

DESCRIPTION

These are a record of the hubs an event passes through. Most recent hub is the first one in the list.

FACET FIELDS

`$string = $trace->{details}`

`$string = $trace->details()`

The hub class or subclass

`$int = $trace->{pid}`

`$int = $trace->pid()`

PID of the hub this event was sent to.

`$int = $trace->{tid}`

`$int = $trace->tid()`

The thread ID of the hub the event was sent to.

`$hid = $trace->{hid}`

`$hid = $trace->hid()`

The ID of the hub that the event was sent to.

`$huuid = $trace->{huuid}`

`$huuid = $trace->huuid()`

The UUID of the hub that the event was sent to.

`$int = $trace->{nested}`

`$int = $trace->nested()`

How deeply nested the hub was.

`$bool = $trace->{buffered}`

`$bool = $trace->buffered()`

True if the event was buffered and not sent to the formatter independent of a parent

(This should never be set when nested is 0 or "undef").

## SOURCE

The source code repository for Test2 can be found at

<http://github.com/Test-More/test-more/>.

## MAINTAINERS

Chad Granum <[exodist@cpan.org](mailto:exodist@cpan.org)>

## AUTHORS

Chad Granum <[exodist@cpan.org](mailto:exodist@cpan.org)>

## COPYRIGHT

Copyright 2020 Chad Granum <[exodist@cpan.org](mailto:exodist@cpan.org)>.

This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

See <http://dev.perl.org/licenses/>

