



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'Test2::EventFacet::Parent.3perl'***

***\$ man Test2::EventFacet::Parent.3perl***

Test2::EventFacet::Parent(3perl) Perl Programmers Reference GuideTest2::EventFacet::Parent(3perl)

#### NAME

Test2::EventFacet::Parent - Facet for events contains other events

#### DESCRIPTION

This facet is used when an event contains other events, such as a subtest.

#### FIELDS

`$string = $parent->{details}`

`$string = $parent->details()`

Human readable description of the event.

`$hid = $parent->{hid}`

`$hid = $parent->hid()`

Hub ID of the hub that is represented in the parent-child relationship.

`$arrayref = $parent->{children}`

`$arrayref = $parent->children()`

Arrayref containing the facet-data hashes of events nested under this one.

To get the actual events you need to get them from the parent event directly

`$bool = $parent->{buffered}`

`$bool = $parent->buffered()`

True if the subtest is buffered (meaning the formatter has probably not seen them yet).

#### SOURCE

The source code repository for Test2 can be found at

<http://github.com/Test-More/test-more/>.

## MAINTAINERS

Chad Granum <exodist@cpan.org>

## AUTHORS

Chad Granum <exodist@cpan.org>

## COPYRIGHT

Copyright 2020 Chad Granum <exodist@cpan.org>.

This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

See <http://dev.perl.org/licenses/>

perl v5.34.0

2023-11-23

Test2::EventFacet::Parent(3perl)