



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Test2::EventFacet::Render.3perl'

\$ man Test2::EventFacet::Render.3perl

Test2::EventFacet::Render(3perl) Perl Programmers Reference GuideTest2::EventFacet::Render(3perl)

NAME

Test2::EventFacet::Render - Facet that dictates how to render an event.

DESCRIPTION

This facet is used to dictate how the event should be rendered by the standard test2 rendering tools. If this facet is present then ONLY what is specified by it will be rendered. It is assumed that anything important or note-worthy will be present here, no other facets will be considered for rendering/display.

This facet is a list type, you can add as many items as needed.

FIELDS

`$string = $render->[#]->{details}`

`$string = $render->[#]->details()`

Human readable text for display.

`$string = $render->[#]->{tag}`

`$string = $render->[#]->tag()`

Tag that should prefix/identify the main text.

`$string = $render->[#]->{facet}`

`$string = $render->[#]->facet()`

Optional, if the display text was generated from another facet this should state what facet it was.

`$mode = $render->[#]->{mode}`

`$mode = $render->[#]->mode()`

calculated

Calculated means the facet was generated from another facet. Calculated facets may be cleared and regenerated whenever the event state changes.

replace

Replace means the facet is intended to replace the normal rendering of the event.

SOURCE

The source code repository for Test2 can be found at

<http://github.com/Test-More/test-more/>.

MAINTAINERS

Chad Granum <exodist@cpan.org>

AUTHORS

Chad Granum <exodist@cpan.org>

COPYRIGHT

Copyright 2020 Chad Granum <exodist@cpan.org>.

This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

See <http://dev.perl.org/licenses/>

perl v5.34.0

2023-11-23

Test2::EventFacet::Render(3perl)