



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'Test2::Hub::Subtest.3perl'

\$ man Test2::Hub::Subtest.3perl

Test2::Hub::Subtest(3perl) Perl Programmers Reference Guide Test2::Hub::Subtest(3perl)

NAME

Test2::Hub::Subtest - Hub used by subtests

DESCRIPTION

Subtests make use of this hub to route events.

TOGGLES

`$bool = $hub->manual_skip_all`

`$hub->set_manual_skip_all($bool)`

The default is false.

Normally a skip-all plan event will cause a subtest to stop executing. This is accomplished via "last LABEL" to a label inside the subtest code. Most of the time this is perfectly fine. There are times however where this flow control causes bad things to happen.

This toggle lets you turn off the abort logic for the hub. When this is toggled to true you are responsible for ensuring no additional events are generated.

SOURCE

The source code repository for Test2 can be found at

<http://github.com/Test-More/test-more/>.

MAINTAINERS

Chad Granum <exodist@cpan.org>

AUTHORS

Chad Granum <exodist@cpan.org>

COPYRIGHT

Copyright 2020 Chad Granum <exodist@cpan.org>.

This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

See <http://dev.perl.org/licenses/>

perl v5.34.0

2023-11-23

Test2::Hub::Subtest(3perl)