



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'URI::WithBase.3pm'***

***\$ man URI::WithBase.3pm***

URI::WithBase(3pm)      User Contributed Perl Documentation      URI::WithBase(3pm)

**NAME**

URI::WithBase - URIs which remember their base

**SYNOPSIS**

```
$u1 = URI::WithBase->new($str, $base);  
$u2 = $u1->abs;  
  
$base = $u1->base;  
$u1->base( $new_base )
```

**DESCRIPTION**

This module provides the "URI::WithBase" class. Objects of this class are like "URI" objects, but can keep their base too. The base represents the context where this URI was found and can be used to absolutize or relativize the URI. All the methods described in URI are supported for "URI::WithBase" objects.

The methods provided in addition to or modified from those of "URI" are:

```
$uri = URI::WithBase->new($str, [$base])
```

The constructor takes an optional base URI as the second argument. If provided, this argument initializes the base attribute.

`$uri->base( [$new_base] )`

Can be used to get or set the value of the base attribute. The return value, which is the old value, is a URI object or "undef".

`$uri->abs( [$base_uri] )`

The `$base_uri` argument is now made optional as the object carries its base with it. A new object is returned even if `$uri` is already absolute (while plain URI objects simply return themselves in that case).

`$uri->rel( [$base_uri] )`

The `$base_uri` argument is now made optional as the object carries its base with it. A new object is always returned.

SEE ALSO

URI

COPYRIGHT

Copyright 1998-2002 Gisle Aas.

perl v5.32.1

2021-10-26

URI::WithBase(3pm)