



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'Unicode::Collate::CJK::GB2312.3perl'***

***\$ man Unicode::Collate::CJK::GB2312.3perl***

Unicode::Collate::CJK::GB2312(3pePerl Programmers Reference GUnicode::Collate::CJK::GB2312(3perl)

NAME

Unicode::Collate::CJK::GB2312 - weighting CJK Unified Ideographs for Unicode::Collate

SYNOPSIS

```
use Unicode::Collate;
```

```
use Unicode::Collate::CJK::GB2312;
```

```
my $collator = Unicode::Collate->new(
```

```
    overrideCJK => \&Unicode::Collate::CJK::GB2312::weightGB2312
```

```
);
```

DESCRIPTION

"Unicode::Collate::CJK::GB2312" provides "weightGB2312()", that is adequate for

"overrideCJK" of "Unicode::Collate" and makes tailoring of CJK Unified Ideographs in the

order of CLDR's gb2312han ordering.

CAVEAT

The gb2312han ordering includes 5 code points in private use area (E2D8..E2DC), that can't

utilize "weightGB2312()" for collation. For them, use "entry" instead.

SEE ALSO

CLDR - Unicode Common Locale Data Repository

<<http://cldr.unicode.org/>>

Unicode Locale Data Markup Language (LDML) - UTS #35

<<http://www.unicode.org/reports/tr35/>>

Unicode::Collate

Unicode::Collate::Locale

perl v5.34.0

2023-11-23

Unicode::Collate::CJK::GB2312(3perl)