



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'XtRemoveWorkProc.3'

\$ man XtRemoveWorkProc.3

XtAppAddWorkProc(3) XT FUNCTIONS XtAppAddWorkProc(3)

NAME

XtAppAddWorkProc, XtRemoveWorkProc - Add and remove background processing procedures

SYNTAX

```
#include <X11/Intrinsic.h>
```

```
XtWorkProcId XtAppAddWorkProc(XtAppContext app_context, XtWorkProc proc, XtPointer  
client_data);
```

```
void XtRemoveWorkProc(XtWorkProcId id);
```

ARGUMENTS

app_context

Specifies the application context that identifies the application.

client_data

Specifies the argument that is to be passed to the specified procedure when it is called.

proc Specifies the procedure that is to be called.

id Specifies which work procedure to remove.

DESCRIPTION

The XtAppAddWorkProc function adds the specified work procedure for the application identified by app_context.

The XtRemoveWorkProc function explicitly removes the specified background work procedure.

SEE ALSO

XtAppNextEvent(3)

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.2.1

XtAppAddWorkProc(3)