



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'aa-remove-unknown.8'

\$ man aa-remove-unknown.8

AA-REMOVE-UNKNOWN(8)

AppArmor

AA-REMOVE-UNKNOWN(8)

NAME

aa-remove-unknown - remove unknown AppArmor profiles

SYNOPSIS

aa-remove-unknown [option]

DESCRIPTION

aa-remove-unknown will inventory all profiles in /etc/apparmor.d/, compare that list to the profiles currently loaded into the kernel, and then remove all of the loaded profiles that were not found in /etc/apparmor.d/. It will also report the name of each profile that it removes on standard out.

OPTIONS

-h, --help

displays a short usage statement.

-n dry run; only prints the names of profiles that would be removed

EXAMPLES

\$ sudo ./aa-remove-unknown -n

Would remove 'test//null-/usr/bin/whoami'

Would remove 'test'

```
$ sudo ./aa-remove-unknown
Removing 'test//null-/usr/bin/whoami'
Removing 'test'
```

BUGS

None. Please report any you find to Gitlab at
<<https://gitlab.com/apparmor/apparmor/-/issues>>.

SEE ALSO

[apparmor\(7\)](#)

AppArmor 3.0.4

2023-06-05

AA-REMOVE-UNKNOWN(8)