

apache2ctl(8)

System Manager's Manual

apache2ctl(8)

NAME

apache2ctl - Apache HTTP server control interface

SYNOPSIS

When acting in SysV init mode, apache2ctl takes simple, one-word commands, defined below.

apachectl command

apache2ctl command

When acting in pass-through mode, apache2ctl can take all the arguments available for the httpd binary.

apachectl [httpd-argument]

apache2ctl [httpd-argument]

DESCRIPTION

apache2ctl is a front end to the Apache HyperText Transfer Protocol (HTTP) server. It is designed to help the administrator control the functioning of the Apache apache2 daemon.

Linux UBUNTU Manual Pages

NOTE: The default Debian configuration requires the environment variables `APACHE_RUN_USER`, `APACHE_RUN_GROUP`, and `APACHE_PID_FILE` to be set in `/etc/apache2/envvars`.

The `apache2ctl` script returns a 0 exit value on success, and `>0` if an error occurs. For more details, view the comments in the script.

OPTIONS

The command can be any one or more of the following options:

start Start the Apache daemon. Gives an error if it is already running.

stop Stops the Apache daemon.

restart Restarts the Apache daemon by sending it a `SIGHUP`. If the daemon is not running, it is started. This command automatically checks the configuration files via `configtest` before initiating the restart to catch the most obvious errors. However, it is still possible for the daemon to die because of problems with the configuration.

to work, you need to have `mod_status` enabled on your server and a text-based browser such as `lynx` available on your system. The URL used to access the status report can be set by setting the `APACHE_STATUSURL` variable in `/etc/apache2/envvars`.

status Displays a brief status report. Similar to the `fullstatus` option, except that the list of requests currently being served is omitted.

graceful Gracefully restarts the Apache daemon by sending it a `SIGUSR1`. If the daemon is not running, it is started. This differs from a normal restart in that currently open connections are not aborted. A side effect is that old log files will not be closed immediately. This means that if used in a log rotation script, a substantial delay may be necessary to ensure that the old log files are closed before processing them. This command automatically checks the configuration files via `apache2ctl configtest` before initiating the restart to catch the most obvious errors. However, it is still possible for the daemon to die because of problems with the configuration.

Linux UBUNTU Manual Pages

from a normal stop in that currently open connections are not aborted. A side effect is that old log files will not be closed immediately.

configtest Run a configuration file syntax test. It parses the configuration files and either reports Syntax Ok or information about the particular syntax error. This test does not catch all errors.

help Displays a short help message.

The following option was available in earlier versions but has been removed.

startssl To start httpd with SSL support, you should edit your configuration file to include the relevant directives and then use the normal `apache2ctl start`.

ENVIRONMENT

The behaviour of `apache2ctl` can be influenced with these environment

variables: `APACHE_HTTPD`, `APACHE_LYNX`, `APACHE_STATUSURL`,
`APACHE_ULIMIT_MAX_FILES`, `APACHE_RUN_DIR`, `APACHE_LOCK_DIR`,

`APACHE_RUN_USER`, `APACHE_ARGUMENTS`, `APACHE_ENVVARS`. See the
Page 4/5

comments in

Linux UBUNTU Manual Pages

set in `/etc/apache2/envvars`.

SEE ALSO

`apache2(8)`, `/usr/share/doc/apache2/README.Debian.gz`

April 2008

`apache2ctl(8)`