



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'appres.1'

\$ man appres.1

APPRES(1) General Commands Manual APPRES(1)

NAME

appres - list X application resource database

SYNOPSIS

appres [class [instance]] [-1] [-V] [toolkitoptions]

DESCRIPTION

The appres program prints the resources seen by an application (or subhierarchy of an application) with the specified class and instance names. It can be used to determine which resources a particular program will load. For example,

```
% appres XTerm
```

will list the resources that any xterm program will load. If no application class is specified, the class -AppResTest- is used.

To match a particular instance name, specify an instance name explicitly after the class name, or use the normal Xt toolkit option. For example,

```
% appres XTerm myxterm
```

or

```
% appres XTerm -name myxterm
```

To list resources that match a subhierarchy of an application, specify hierarchical class and instance names. The number of class and instance components must be equal, and the instance name should not be specified with a toolkit option. For example,

```
% appres Xman.TopLevelShell.Form xman.topBox.form
```

will list the resources of widgets of xman topBox hierarchy. To list just the resources matching a specific level in the hierarchy, use the -1 option. For example,

```
% appres XTerm.VT100 xterm.vt100 -1
```

will list the resources matching the xterm vt100 widget.

The -V option prints the appres command version and exits.

SEE ALSO

X(7), xrdp(1), listres(1)

AUTHOR

Jim Fulton, MIT X Consortium

X Version 11

appres 1.0.5

APPRES(1)