

APT-CONFIG(8)

APT

APT-CONFIG(8)

NAME

apt-config - APT Configuration Query program

SYNOPSIS

```
apt-config [--empty] [--format '%f "%v";%n'] [-o=config_string]
          [-c=config_file] {shell | dump | {-v | --version} |
          {-h | --help}}
```

DESCRIPTION

apt-config is an internal program used by various portions of the APT suite to provide consistent configurability. It accesses the main configuration file `/etc/apt/apt.conf` in a manner that is easy to use for scripted applications.

Unless the `-h`, or `--help` option is given, one of the commands below must be present.

shell

`shell` is used to access the configuration information from a shell script. It is given pairs of arguments, the first being a shell variable and the second the configuration value to query. As output

shell script it should be used as follows:

```
OPTS="-f"
```

```
RES=`apt-config shell OPTS MyApp::options`
```

```
eval $RES
```

This will set the shell environment variable `$OPTS` to the value of `MyApp::options` with a default of `-f`.

The configuration item may be postfixed with a `/[fdbi]`. `f` returns file names, `d` returns directories, `b` returns true or false and `i` returns an integer. Each of the returns is normalized and verified internally.

dump

Just show the contents of the configuration space.

OPTIONS

All command line options may be set using the configuration file, the descriptions indicate the configuration option to set. For boolean options you can override the config file by using something like `-f`, `--no-f`, `-f=no` or several other variations.

--empty

Include options which have an empty value. This is the default, so

--format '%f "%v";%n'

Defines the output of each config option. %t will be replaced with its individual name, %f with its full hierarchical name and %v with its value. Use uppercase letters and special characters in the value will be encoded to ensure that it can e.g. be safely used in a quoted-string as defined by RFC822. Additionally %n will be replaced by a newline, and %N by a tab. A % can be printed by using %%.

-h, --help

Show a short usage summary.

-v, --version

Show the program version.

-c, --config-file

Configuration File; Specify a configuration file to use. The program will read the default configuration file and then this configuration file. If configuration settings need to be set before the default configuration files are parsed specify a file with the APT_CONFIG environment variable. See apt.conf(5) for syntax information.

Set a Configuration Option; This will set an arbitrary configuration option. The syntax is `-o Foo::Bar=bar`. `-o` and `--option` can be used multiple times to set different options.

SEE ALSO

`apt.conf(5)`

DIAGNOSTICS

`apt-config` returns zero on normal operation, decimal 100 on error.

BUGS

APT bug page[1]. If you wish to report a bug in APT, please see `/usr/share/doc/debian/bug-reporting.txt` or the `reportbug(1)` command.

AUTHORS

Jason Gunthorpe

APT team

NOTES

1. APT bug page

<https://bugs.debian.org/src:apt>