

APT.CONF(5)

APT

APT.CONF(5)

NAME

apt.conf - Configuration file for APT

DESCRIPTION

`/etc/apt/apt.conf` is the main configuration file shared by all the tools in the APT suite of tools, though it is by no means the only place options can be set. The suite also shares a common command line parser to provide a uniform environment.

When an APT tool starts up it will read the configuration files in the following order:

- 1. the file specified by the `APT_CONFIG` environment variable (if any)**
- 2. all files in `Dir::Etc::Parts` in alphanumeric ascending order which have either no or "conf" as filename extension and which only contain alphanumeric, hyphen (-), underscore (_) and period (.) characters. Otherwise APT will print a notice that it has ignored a file, unless that file matches a pattern in the `Dir::Ignore-Files-Silently` configuration list - in which case it will be silently ignored.**

4. all options set in the binary specific configuration subtree are moved into the root of the tree.
5. the command line options are applied to override the configuration directives or to load even more configuration files.

SYNTAX

The configuration file is organized in a tree with options organized into functional groups. Option specification is given with a double colon notation; for instance `APT::Get::Assume-Yes` is an option within the APT tool group, for the Get tool. Options do not inherit from their parent groups.

Syntactically the configuration language is modeled after what the ISC tools such as `bind` and `dhcp` use. Lines starting with `//` are treated as comments (ignored), as well as all text between `/*` and `*/`, just like C/C++ comments. Lines starting with `#` are also treated as comments. Each line is of the form `APT::Get::Assume-Yes "true";`. The quotation marks and trailing semicolon are required. The value must be on one line, and there is no kind of string concatenation. Values must not include backslashes or extra quotation marks. Option names are made up of alphanumeric characters and the characters `"/-:._+ "`. A new scope can be opened with curly braces, like this:

```
APT {  
  Get {  
    Assume-Yes "true";  
    Fix-Broken "true";  
  };  
};
```

with newlines placed to make it more readable. Lists can be created by opening a scope and including a single string enclosed in quotes followed by a semicolon. Multiple entries can be included, separated by a semicolon.

```
DPkg::Pre-Install-Pkgs {"/usr/sbin/dpkg-preconfigure --apt"};
```

In general the sample configuration file `/usr/share/doc/apt/examples/configure-index` is a good guide for how it should look.

Case is not significant in names of configuration items, so in the previous example you could use `dpkg::pre-install-pkgs`.

Names for the configuration items are optional if a list is defined as can be seen in the `DPkg::Pre-Install-Pkgs` example above. If you don't specify a name a new entry will simply add a new option to the list. If

other option by reassigning a new value to the option.

Two special commands are defined: `#include` (which is deprecated and not supported by alternative implementations) and `#clear`. `#include` will include the given file, unless the filename ends in a slash, in which case the whole directory is included. `#clear` is used to erase a part of the configuration tree. The specified element and all its descendants are erased. (Note that these lines also need to end with a semicolon.)

The `#clear` command is the only way to delete a list or a complete scope. Reopening a scope (or using the syntax described below with an appended `::`) will not override previously written entries. Options can only be overridden by addressing a new value to them - lists and scopes can't be overridden, only cleared.

All of the APT tools take an `-o` option which allows an arbitrary configuration directive to be specified on the command line. The syntax is a full option name (`APT::Get::Assume-Yes` for instance) followed by an equals sign then the new value of the option. To append a new element to a list, add a trailing `::` to the name of the list. (As you might suspect, the scope syntax can't be used on the command line.)

Note that appending items to a list using `::` only works for one item

syntax (which adds `::` implicitly). Using both syntaxes together will trigger a bug which some users unfortunately depend on: an option with the unusual name `:::` which acts like every other option with a name. This introduces many problems; for one thing, users who write multiple lines in this wrong syntax in the hope of appending to a list will achieve the opposite, as only the last assignment for this option `:::` will be used. Future versions of APT will raise errors and stop working if they encounter this misuse, so please correct such statements now while APT doesn't explicitly complain about them.

THE APT GROUP

This group of options controls general APT behavior as well as holding the options for all of the tools.

Architecture

System Architecture; sets the architecture to use when fetching files and parsing package lists. The internal default is the architecture apt was compiled for.

Architectures

All Architectures the system supports. For instance, CPUs implementing the amd64 (also called x86-64) instruction set are also able to execute binaries compiled for the i386 (x86) instruction set. This list is used when fetching files and parsing

architecture (APT::Architecture), and foreign architectures are added to the default list when they are registered via `dpkg --add-architecture`.

Compressor

This scope defines which compression formats are supported, how compression and decompression can be performed if support for this format isn't built into apt directly and a cost-value indicating how costly it is to compress something in this format. As an example the following configuration stanza would allow apt to download and uncompress as well as create and store files with the low-cost `.reversed` file extension which it will pass to the command `rev` without additional commandline parameters for compression and uncompression:

```
APT::Compressor::rev {  
    Name "rev";  
    Extension ".reversed";  
    Binary "rev";  
    CompressArg {};  
    UncompressArg {};  
    Cost "10";  
};
```

List of all build profiles enabled for build-dependency resolution, without the "profile." namespace prefix. By default this list is empty. The `DEB_BUILD_PROFILES` as used by `dpkg-buildpackage(1)` overrides the list notation.

Default-Release

Default release to install packages from if more than one version is available. Contains release name, codename or release version. Examples: 'stable', 'testing', 'unstable', 'bookworm', 'trixie', '4.0', '5.0*'. See also `apt_preferences(5)`.

Snapshot

Snapshot to use for all repositories configured with `Snapshot: yes`. See also `sources.list(5)`, the `--snapshot` option that sets this value, and `Acquire::Snapshots::URI` below.

Ignore-Hold

Ignore held packages; this global option causes the problem resolver to ignore held packages in its decision making.

Clean-Installed

Defaults to on. When turned on the autoclean feature will remove any packages which can no longer be downloaded from the cache. If turned off then packages that are locally installed are also

to reinstall them.

Immediate-Configure

Defaults to on, which will cause APT to install essential and important packages as soon as possible in an install/upgrade operation, in order to limit the effect of a failing `dpkg(1)` call.

If this option is disabled, APT treats an important package in the same way as an extra package: between the unpacking of the package A and its configuration there can be many other unpack or configuration calls for other unrelated packages B, C etc. If these cause the `dpkg(1)` call to fail (e.g. because package B's maintainer scripts generate an error), this results in a system state in which package A is unpacked but unconfigured - so any package depending on A is now no longer guaranteed to work, as its dependency on A is no longer satisfied.

The immediate configuration marker is also applied in the potentially problematic case of circular dependencies, since a dependency with the immediate flag is equivalent to a Pre-Dependency. In theory this allows APT to recognise a situation in which it is unable to perform immediate configuration, abort, and suggest to the user that the option should be temporarily deactivated in order to allow the operation to proceed. Note the use of the word "theory" here; in the real world this problem has

was caused by wrong dependencies of the package in question or by a system in an already broken state; so you should not blindly disable this option, as the scenario mentioned above is not the only problem it can help to prevent in the first place.

Before a big operation like `dist-upgrade` is run with this option disabled you should try to explicitly install the package APT is unable to configure immediately; but please make sure you also report your problem to your distribution and to the APT team with the bug link below, so they can work on improving or correcting the upgrade process.

Force-LoopBreak

Never enable this option unless you really know what you are doing. It permits APT to temporarily remove an essential package to break a Conflicts/Conflicts or Conflicts/Pre-Depends loop between two essential packages. Such a loop should never exist and is a grave bug. This option will work if the essential packages are not tar, gzip, libc, dpkg, dash or anything that those packages depend on.

Cache-Start, Cache-Grow, Cache-Limit

APT uses since version 0.7.26 a resizable memory mapped cache file to store the available information. Cache-Start acts as a hint of the size the cache will grow to, and is therefore the amount of

bytes (~20 MB). Note that this amount of space needs to be available for APT; otherwise it will likely fail ungracefully, so for memory restricted devices this value should be lowered while on systems with a lot of configured sources it should be increased. Cache-Grow defines in bytes with the default of 1048576 (~1 MB) how much the cache size will be increased in the event the space defined by Cache-Start is not enough. This value will be applied again and again until either the cache is big enough to store all information or the size of the cache reaches the Cache-Limit. The default of Cache-Limit is 0 which stands for no limit. If Cache-Grow is set to 0 the automatic growth of the cache is disabled.

Build-Essential

Defines which packages are considered essential build dependencies.

Get

The Get subsection controls the apt-get(8) tool; please see its documentation for more information about the options here.

Cache

The Cache subsection controls the apt-cache(8) tool; please see its documentation for more information about the options here.

The CDRom subsection controls the apt-cdrom(8) tool; please see its documentation for more information about the options here.

NeverAutoRemove

Never autoremove packages that match the regular expression(s).

Protect-Kernels

This option tells apt autoremove that kernels are protected and defaults to true. In case kernels are not protected they are treated as any other package.

VersionedKernelPackages

Define the regular expression(s) for versioned kernel packages. Based on these expressions a rule set is injected into apt similar to APT::NeverAutoRemove regular expressions.

NeverAutoRemove::KernelCount

Keep a custom amount of kernels when autoremoving and defaults to 2, meaning two kernels are kept. Apt will always keep the running kernel and the latest one. If the latest kernel is the same as the running kernel, the second latest kernel is kept. Because of this, any value lower than 2 will be ignored. If you want only the latest kernel, you should set APT::Protect-Kernels to false.

The Acquire group of options controls the download of packages as well as the various "acquire methods" responsible for the download itself (see also `sources.list(5)`).

Check-Date

Security related option defaulting to true, enabling time-related checks. Disabling it means that the machine's time cannot be trusted, and APT will hence disable all time-related checks, such as Check-Valid-Until and verifying that the Date field of a release file is not in the future.

Max-FutureTime

Maximum time (in seconds) before its creation (as indicated by the Date header) that the Release file should be considered valid. The default value is 10. Archive specific settings can be made by appending the label of the archive to the option name. Preferably, the same can be achieved for specific `sources.list(5)` entries by using the Date-Max-Future option there.

Check-Valid-Until

Security related option defaulting to true, as giving a Release file's validation an expiration date prevents replay attacks over a long timescale, and can also for example help users to identify mirrors that are no longer updated - but the feature depends on the

are encouraged to create Release files with the Valid-Until header, but if they don't or a stricter value is desired the Max-ValidTime option below can be used. The Check-Valid-Until option of sources.list(5) entries should be preferred to disable the check selectively instead of using this global override.

Max-ValidTime

Maximum time (in seconds) after its creation (as indicated by the Date header) that the Release file should be considered valid. If the Release file itself includes a Valid-Until header the earlier date of the two is used as the expiration date. The default value is 0 which stands for "valid forever". Archive specific settings can be made by appending the label of the archive to the option name. Preferably, the same can be achieved for specific sources.list(5) entries by using the Valid-Until-Max option there.

Min-ValidTime

Minimum time (in seconds) after its creation (as indicated by the Date header) that the Release file should be considered valid. Use this if you need to use a seldom updated (local) mirror of a more frequently updated archive with a Valid-Until header instead of completely disabling the expiration date checking. Archive specific settings can and should be used by appending the label of the archive to the option name. Preferably, the same can be achieved

option there.

AllowTLS

Allow use of the internal TLS support in the http method. If set to false, this completely disables support for TLS in apt's own methods (excluding the curl-based https method). No TLS-related functions will be called anymore.

PDiffs

Try to download deltas called PDiffs for indexes (like Packages files) instead of downloading whole ones. True by default.

Preferably, this can be set for specific sources.list(5) entries or index files by using the PDiffs option there.

Two sub-options to limit the use of PDiffs are also available:

FileLimit can be used to specify a maximum number of PDiff files should be downloaded to update a file. SizeLimit on the other hand is the maximum percentage of the size of all patches compared to the size of the targeted file. If one of these limits is exceeded the complete file is downloaded instead of the patches.

By-Hash

Try to download indexes via an URI constructed from a hashsum of the expected file rather than downloaded via a well-known stable

indicates no support for it. Usage can be forced with the special value "force". Preferably, this can be set for specific sources.list(5) entries or index files by using the By-Hash option there.

Queue-Mode

Queuing mode; Queue-Mode can be one of host or access which determines how APT parallelizes outgoing connections. host means that one connection per target host will be opened, access means that one connection per URI type will be opened.

Retries

Number of retries to perform. If this is non-zero APT will retry failed files the given number of times.

Source-Symlinks

Use symlinks for source archives. If set to true then source archives will be symlinked when possible instead of copying. True is the default.

http https

The options in these scopes configure APT's acquire transports for the protocols HTTP and HTTPS and are documented in the apt-transport-http(1) and apt-transport-https(1) manpages respectively.

ftp

`ftp::Proxy` sets the default proxy to use for FTP URIs. It is in the standard form of `ftp://[[user][:pass]@]host[:port]/`. Per host proxies can also be specified by using the form `ftp::Proxy::<host>` with the special keyword `DIRECT` meaning to use no proxies. If no one of the above settings is specified, `ftp_proxy` environment variable will be used. To use an FTP proxy you will have to set the `ftp::ProxyLogin` script in the configuration file. This entry specifies the commands to send to tell the proxy server what to connect to. Please see `/usr/share/doc/apt/examples/configure-index` for an example of how to do this. The substitution variables representing the corresponding URI component are `$(PROXY_USER)`, `$(PROXY_PASS)`, `$(SITE_USER)`, `$(SITE_PASS)`, `$(SITE)` and `$(SITE_PORT)`.

The option `timeout` sets the timeout timer used by the method; this value applies to the connection as well as the data timeout.

Several settings are provided to control passive mode. Generally it is safe to leave passive mode on; it works in nearly every environment. However, some situations require that passive mode be disabled and port mode FTP used instead. This can be done globally or for connections that go through a proxy or for a specific host (see the sample config file for examples).

It is possible to proxy FTP over HTTP by setting the `ftp_proxy` environment variable to an HTTP URL - see the discussion of the `http` method above for syntax. You cannot set this in the configuration file and it is not recommended to use FTP over HTTP due to its low efficiency.

The setting `ForceExtended` controls the use of RFC2428 EPSV and EPRT commands. The default is `false`, which means these commands are only used if the control connection is IPv6. Setting this to `true` forces their use even on IPv4 connections. Note that most FTP servers do not support RFC2428.

cdrom

For URIs using the `cdrom` method, the only configurable option is the mount point, `cdrom::Mount`, which must be the mount point for the CD-ROM (or DVD, or whatever) drive as specified in `/etc/fstab`.

It is possible to provide alternate mount and unmount commands if your mount point cannot be listed in the `fstab`. The syntax is to

put

```
/cdrom/::Mount "foo";
```

within the `cdrom` block. It is important to have the trailing slash.

Unmount commands can be specified using `UMount`.

gpgv

For GPGV URIs the only configurable option is `gpgv::Options`, which passes additional parameters to `gpgv`.

CompressionTypes

List of compression types which are understood by the acquire methods. Files like Packages can be available in various compression formats. By default the acquire methods can decompress and recompress many common formats like `xz` and `gzip`; with this scope the supported formats can be queried, modified as well as support for more formats added (see also `APT::Compressor`). The syntax for this is:

```
Acquire::CompressionTypes::FileExtension "Methodname";
```

Also, the `Order` subgroup can be used to define in which order the acquire system will try to download the compressed files. The acquire system will try the first and proceed with the next compression type in this list on error, so to prefer one over the other type simply add the preferred type first - types not already added will be implicitly appended to the end of the list, so e.g.

```
Acquire::CompressionTypes::Order:: "gz";
```

compression formats. If xz should be preferred over gzip and bzip2 the configure setting should look like this:

```
Acquire::CompressionTypes::Order { "xz"; "gz"; };
```

It is not needed to add bz2 to the list explicitly as it will be added automatically.

Note that the `Dir::Bin::Methodname` will be checked at run time. If this option has been set and support for this format isn't directly built into apt, the method will only be used if this file exists; e.g. for the bzip2 method (the inbuilt) setting is:

```
Dir::Bin::bzip2 "/bin/bzip2";
```

Note also that list entries specified on the command line will be added at the end of the list specified in the configuration files, but before the default entries. To prefer a type in this case over the ones specified in the configuration files you can set the option `direct` - not in list style. This will not override the defined list; it will only prefix the list with this type.

The special type `uncompressed` can be used to give uncompressed files a preference, but note that most archives don't provide

GzipIndexes

When downloading gzip compressed indexes (Packages, Sources, or Translations), keep them gzip compressed locally instead of unpacking them. This saves quite a lot of disk space at the expense of more CPU requirements when building the local package caches. False by default.

Languages

The Languages subsection controls which Translation files are downloaded and in which order APT tries to display the description-translations. APT will try to display the first available description in the language which is listed first.

Languages can be defined with their short or long language codes.

Note that not all archives provide Translation files for every language - the long language codes are especially rare.

The default list includes "environment" and "en". "environment" has a special meaning here: it will be replaced at runtime with the language codes extracted from the LC_MESSAGES environment variable.

It will also ensure that these codes are not included twice in the list. If LC_MESSAGES is set to "C" only the Translation-en file (if available) will be used. To force APT to use no Translation file

use the setting `Acquire::Languages=none`. "none" is another special

file. This tells APT to download these translations too, without actually using them unless the environment specifies the languages.

So the following example configuration will result in the order "en, de" in an English locale or "de, en" in a German one. Note that "fr" is downloaded, but not used unless APT is used in a French locale (where the order would be "fr, de, en").

```
Acquire::Languages { "environment"; "de"; "en"; "none"; "fr"; };
```

Note: To prevent problems resulting from APT being executed in different environments (e.g. by different users or by other programs) all Translation files which are found in `/var/lib/apt/lists/` will be added to the end of the list (after an implicit "none").

ForceIPv4

When downloading, force to use only the IPv4 protocol.

ForceIPv6

When downloading, force to use only the IPv6 protocol.

MaxReleaseFileSize

The maximum file size of Release/Release.gpg/InRelease files. The default is 10MB.

EnableSrvRecords

This option controls if apt will use the DNS SRV server record as specified in RFC 2782 to select an alternative server to connect to. The default is "true".

AllowInsecureRepositories

Allow update operations to load data files from repositories without sufficient security information. The default value is "false". Concept, implications as well as alternatives are detailed in apt-secure(8).

AllowWeakRepositories

Allow update operations to load data files from repositories which provide security information, but these are deemed no longer cryptographically strong enough. The default value is "false". Concept, implications as well as alternatives are detailed in apt-secure(8).

AllowDowngradeToInsecureRepositories

Allow that a repository that was previously gpg signed to become unsigned during an update operation. When there is no valid signature for a previously trusted repository apt will refuse the update. This option can be used to override this protection. You almost certainly never want to enable this. The default is false.

secure(8).

Changelogs::URI scope

Acquiring changelogs can only be done if an URI is known from where to get them. Preferable the Release file indicates this in a 'Changelogs' field. If this isn't available the Label/Origin field of the Release file is used to check if a

Acquire::Changelogs::URI::Label::LABEL or

Acquire::Changelogs::URI::Origin::ORIGIN option exists and if so

this value is taken. The value in the Release file can be

overridden with Acquire::Changelogs::URI::Override::Label::LABEL or

Acquire::Changelogs::URI::Override::Origin::ORIGIN. The value

should be a normal URI to a text file, except that package specific

data is replaced with the placeholder @CHANGE_PATH@. The value for

it is: 1. if the package is from a component (e.g. main) this is

the first part otherwise it is omitted, 2. the first letter of

source package name, except if the source package name starts with

'lib' in which case it will be the first four letters. 3. The

complete source package name. 4. the complete name again and 5. the

source version. The first (if present), second, third and fourth

part are separated by a slash (/) and between the fourth and

fifth part is an underscore ('_'). The special value 'no' is

available for this option indicating that this source can't be used

to acquire changelog files from. Another source will be tried if

Snapshots::URI scope

Like changelogs, snapshots can only be acquired if an URI is known from where to get them. Preferable the Release file indicates this in a 'Snapshots' field. If this isn't available the Label/Origin field of the Release file is used to check if a `Acquire::Snapshots::URI::Label::LABEL` or `Acquire::Snapshots::URI::Origin::ORIGIN` option exists and if so this value is taken. The value in the Release file can be overridden with `Acquire::Snapshots::URI::Override::Label::LABEL` or `Acquire::Snapshots::URI::Override::Origin::ORIGIN`. The value should be a normal URI to a directory, except that the snapshot ID replaced with the placeholder `@SNAPSHOTID`. The special value 'no' is available for this option indicating that this source cannot be used to acquire snapshots from. Another source will be tried if available in this case.

BINARY SPECIFIC CONFIGURATION

Especially with the introduction of the apt binary it can be useful to set certain options only for a specific binary as even options which look like they would effect only a certain binary like `APT::Get::Show-Versions` effect apt-get as well as apt.

Setting an option for a specific binary only can be achieved by setting

APT::Get::Show-Versions for the apt only can e.g. be done by setting **Binary::apt::APT::Get::Show-Versions** instead.

Note that as seen in the **DESCRIPTION** section further above you can't set binary-specific options on the commandline itself nor in configuration files loaded via the commandline.

DIRECTORIES

The **Dir::State** section has directories that pertain to local state information. **lists** is the directory to place downloaded package lists in and **status** is the name of the **dpkg(1)** status file. **preferences** is the name of the APT preferences file. **Dir::State** contains the default directory to prefix on all sub-items if they do not start with **/** or **./**.

Dir::Cache contains locations pertaining to local cache information, such as the two package caches **srcpkgcache** and **pkgcache** as well as the location to place downloaded archives, **Dir::Cache::archives**. Generation of caches can be turned off by setting **pkgcache** or **srcpkgcache** to **""**.

This will slow down startup but save disk space. It is probably preferable to turn off the **pkgcache** rather than the **srcpkgcache**. Like **Dir::State** the default directory is contained in **Dir::Cache**

Dir::Etc contains the location of configuration files, **sourcelist** gives the location of the sourcelist and **main** is the default configuration

specified by `APT_CONFIG`).

The `Dir::Parts` setting reads in all the config fragments in lexical order from the directory specified. After this is done then the main config file is loaded.

Binary programs are pointed to by `Dir::Bin`. `Dir::Bin::Methods` specifies the location of the method handlers and `gzip`, `bzip2`, `lzma`, `dpkg`, `apt-get` `dpkg-source` `dpkg-buildpackage` and `apt-cache` specify the location of the respective programs.

The configuration item `RootDir` has a special meaning. If set, all paths will be relative to `RootDir`, even paths that are specified absolutely. So, for instance, if `RootDir` is set to `/tmp/staging` and `Dir::State::status` is set to `/var/lib/dpkg/status`, then the status file will be looked up in `/tmp/staging/var/lib/dpkg/status`. If you want to prefix only relative paths, set `Dir` instead.

The `Ignore-Files-Silently` list can be used to specify which files APT should silently ignore while parsing the files in the fragment directories. Per default a file which ends with `.disabled`, `~`, `.bak` or `.dpkg-[a-z]+` is silently ignored. As seen in the last default value these patterns can use regular expression syntax.

When APT is used as a `dselect(1)` method several configuration directives control the default behavior. These are in the `DSelect` section.

Clean

Cache Clean mode; this value may be one of `always`, `prompt`, `auto`, `pre-auto` and `never`. `always` and `prompt` will remove all packages from the cache after upgrading, `prompt` (the default) does so conditionally. `auto` removes only those packages which are no longer downloadable (replaced with a new version for instance). `pre-auto` performs this action before downloading new packages.

options

The contents of this variable are passed to `apt-get(8)` as command line options when it is run for the install phase.

Updateoptions

The contents of this variable are passed to `apt-get(8)` as command line options when it is run for the update phase.

PromptAfterUpdate

If true the `[U]pdate` operation in `dselect(1)` will always prompt to continue. The default is to prompt only on error.

Several configuration directives control how APT invokes `dpkg(1)`. These are in the `DPkg` section.

options

This is a list of options to pass to `dpkg(1)`. The options must be specified using the list notation and each list item is passed as a single argument to `dpkg(1)`.

Path

This is a string that defines the `PATH` environment variable used when running `dpkg`. It may be set to any valid value of that environment variable; or the empty string, in which case the variable is not changed.

Pre-Invoke, Post-Invoke

This is a list of shell commands to run before/after invoking `dpkg(1)`. Like options this must be specified in list notation. The commands are invoked in order using `/bin/sh`; should any fail APT will abort.

Pre-Install-Pkgs

This is a list of shell commands to run before invoking `dpkg(1)`. Like options this must be specified in list notation. The commands are invoked in order using `/bin/sh`; should any fail APT will abort.

install to the commands, one per line on the requested file descriptor, defaulting to standard input.

Version 2 of this protocol sends more information through the requested file descriptor: a line with the text `VERSION 2`, the APT configuration space, and a list of package actions with filename and version information.

Each configuration directive line has the form `key=value`. Special characters (equal signs, newlines, nonprintable characters, quotation marks, and percent signs in key and newlines, nonprintable characters, and percent signs in value) are %-encoded. Lists are represented by multiple `key::=value` lines with the same key. The configuration section ends with a blank line.

Package action lines consist of five fields in Version 2: package name (without architecture qualification even if foreign), old version, direction of version change (< for upgrades, > for downgrades, = for no change), new version, action. The version fields are "-" for no version at all (for example when installing a package for the first time; no version is treated as earlier than any real version, so that is an upgrade, indicated as - < 1.23.4). The action field is `***CONFIGURE***` if the package is being configured, `***REMOVE***` if it is being removed, or the filename of

In Version 3 after each version field follows the architecture of this version, which is "-" if there is no version, and a field showing the MultiArch type "same", "foreign", "allowed" or "none". Note that "none" is an incorrect typename which is just kept to remain compatible, it should be read as "no" and users are encouraged to support both.

The version of the protocol to be used for the command `cmd` can be chosen by setting `DPkg::Tools::options::cmd::Version` accordingly, the default being version 1. If APT isn't supporting the requested version it will send the information in the highest version it has support for instead.

The file descriptor to be used to send the information can be requested with `DPkg::Tools::options::cmd::InfoFD` which defaults to 0 for standard input and is available since version 0.9.11. Support for the option can be detected by looking for the environment variable `APT_HOOK_INFO_FD` which contains the number of the used file descriptor as a confirmation.

Run-Directory

APT chdirs to this directory before invoking `dpkg(1)`, the default is `/`.

Build-options

These options are passed to `dpkg-buildpackage(1)` when compiling packages; the default is to disable signing and produce all binaries.

DPkg::ConfigurePending

If this option is set APT will call `dpkg --configure --pending` to let `dpkg(1)` handle all required configurations and triggers. This option is activated by default, but deactivating it could be useful if you want to run APT multiple times in a row - e.g. in an installer. In this scenario you could deactivate this option in all but the last run.

PERIODIC AND ARCHIVES OPTIONS

`APT::Periodic` and `APT::Archives` groups of options configure behavior of apt periodic updates, which is done by the `/usr/lib/apt/apt.systemd.daily` script. See the top of this script for the brief documentation of these options.

DEBUG OPTIONS

Enabling options in the `Debug::` section will cause debugging information to be sent to the standard error stream of the program utilizing the apt libraries, or enable special program modes that are primarily useful for debugging the behavior of apt. Most of these

? **Debug::pkgProblemResolver** enables output about the decisions made by `dist-upgrade`, `upgrade`, `install`, `remove`, `purge`.

? **Debug::NoLocking** disables all file locking. This can be used to run some operations (for instance, `apt-get -s install`) as a non-root user.

? **Debug::pkgDPkgPM** prints out the actual command line each time that `apt` invokes `dpkg(1)`.

? **Debug::IdentCdrom** disables the inclusion of `statfs` data in CD-ROM IDs.

A full list of debugging options to `apt` follows.

Debug::Acquire::cdrom

Print information related to accessing `cdrom://` sources.

Debug::Acquire::ftp

Print information related to downloading packages using FTP.

Debug::Acquire::http

Print information related to downloading packages using HTTP.

Debug::Acquire::https

Print information related to downloading packages using HTTPS.

Debug::Acquire::gpgv

Print information related to verifying cryptographic signatures using gpg.

Debug::aptdrom

Output information about the process of accessing collections of packages stored on CD-ROMs.

Debug::Hashes

Output each cryptographic hash that is generated by the apt libraries.

Debug::IdentCDROM

Do not include information from statfs, namely the number of used and free blocks on the CD-ROM filesystem, when generating an ID for a CD-ROM.

Debug::NoLocking

Disable all file locking. For instance, this will allow two instances of `?apt-get update?` to run at the same time.

Log when items are added to or removed from the global download queue.

Debug::pkgAcquire::Auth

Output status messages and errors related to verifying checksums and cryptographic signatures of downloaded files.

Debug::pkgAcquire::Diffs

Output information about downloading and applying package index list diffs, and errors relating to package index list diffs.

Debug::pkgAcquire::RRed

Output information related to patching apt package lists when downloading index diffs instead of full indices.

Debug::pkgAcquire::Worker

Log all interactions with the sub-processes that actually perform downloads.

Debug::pkgAutoRemove

Log events related to the automatically-installed status of packages and to the removal of unused packages.

Debug::pkgDepCache::AutoInstall

automatically installed to resolve dependencies. This corresponds to the initial auto-install pass performed in, e.g., `apt-get install`, and not to the full `apt` dependency resolver; see `Debug::pkgProblemResolver` for that.

`Debug::pkgDepCache::Marker`

Generate debug messages describing which packages are marked as `keep/install/remove` while the `ProblemResolver` does his work. Each addition or deletion may trigger additional actions; they are shown indented two additional spaces under the original entry. The format for each line is `MarkKeep, MarkDelete or MarkInstall` followed by `package-name <a.b.c -> d.e.f | x.y.z> (section)` where `a.b.c` is the current version of the package, `d.e.f` is the version considered for installation and `x.y.z` is a newer version, but not considered for installation (because of a low pin score). The later two can be omitted if there is none or if it is the same as the installed version. `section` is the name of the section the package appears in.

`Debug::pkgDPkgPM`

When invoking `dpkg(1)`, output the precise command line with which it is being invoked, with arguments separated by a single space character.

Output all the data received from `dpkg(1)` on the status file descriptor and any errors encountered while parsing it.

Debug::pkgOrderList

Generate a trace of the algorithm that decides the order in which `apt` should pass packages to `dpkg(1)`.

Debug::pkgPackageManager

Output status messages tracing the steps performed when invoking `dpkg(1)`.

Debug::pkgPolicy

Output the priority of each package list on startup.

Debug::pkgProblemResolver

Trace the execution of the dependency resolver (this applies only to what happens when a complex dependency problem is encountered).

Debug::pkgProblemResolver::ShowScores

Display a list of all installed packages with their calculated score used by the `pkgProblemResolver`. The description of the package is the same as described in `Debug::pkgDepCache::Marker`

Debug::sourceList

`/etc/apt/vendors.list.`

Debug::RunScripts

Display the external commands that are called by apt hooks. This includes e.g. the config options `DPkg::{Pre,Post}-Invoke` or `APT::Update::{Pre,Post}-Invoke`.

EXAMPLES

`/usr/share/doc/apt/examples/configure-index` is a configuration file showing example values for all possible options.

FILES

`/etc/apt/apt.conf`

APT configuration file. Configuration Item: `Dir::Etc::Main`.

`/etc/apt/apt.conf.d/`

APT configuration file fragments. Configuration Item: `Dir::Etc::Parts`.

SEE ALSO

`apt-cache(8)`, `apt-config(8)`, `apt_preferences(5)`.

BUGS

APT bug page[1]. If you wish to report a bug in APT, please see

Linux UBUNTU Manual Pages

AUTHORS

Jason Gunthorpe

APT team

Daniel Burrows <dburrows@debian.org>

Initial documentation of Debug::*.

NOTES

1. APT bug page

<https://bugs.debian.org/src:apt>

APT 2.8.3

21 February 2024

APT.CONF(5)