



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'avahi-browse.1'

\$ man avahi-browse.1

avahi-browse(1) General Commands Manual avahi-browse(1)

NAME

avahi-browse - Browse for mDNS/DNS-SD services using the Avahi daemon

SYNOPSIS

avahi-browse [options] service-type
avahi-browse [options] --all
avahi-browse [options] --browse-domains
avahi-browse [options] --dump-db
avahi-browse-domains [options]

DESCRIPTION

Browse for mDNS/DNS-SD network services and browsing domains using the Avahi daemon.

OPTIONS

Specify a DNS-SD service type (e.g. `_http._tcp`) to browse for on the command line, or `-a` to browse for all available service types. Items that appear on the network are prefixed with "+", items that disappear are prefixed with "-". If `--resolve` is passed items that are resolved are prefixed with "=".

`-a` | `--all`

Browse for all service types registered on the LAN, not just the one specified on the command line.

`-D` | `--browse-domains`

Browse for browsing domains instead for services. `avahi-browse-domains` is equivalent to `avahi-browse --browse-domains`

`-d` | `--domain= DOMAIN`

Browse in the specified domain. If omitted avahi-browse will browse in the default browsing domain (usually: local)

-v | --verbose

Enable verbose mode.

-t | --terminate

Terminate after dumping a more or less complete list.

-c | --cache

Terminate after dumping all entries available in the cache.

-l | --ignore-local

Ignore local services, show only remote services.

-r | --resolve

Automatically resolve services found.

-f | --no-fail

Don't fail if the daemon is not found running. Instead, wait until it appears. If it disconnects, try to reconnect.

-p | --parsable

Make output easily parsable for usage in scripts. If enabled fields are separated by semicolons (;), service names are escaped. It is recommended to combine this with --no-db-lookup.

-k | --no-db-lookup

Don't lookup services types in service type database.

-b | --dump-db

Dump the service type database (may be combined with -k)

-h | --help

Show help.

-V | --version

Show version information.

AUTHORS

The Avahi Developers <avahi (at) lists (dot) freedesktop (dot) org>; Avahi is available from <http://avahi.org/>

SEE ALSO

avahi-publish(1), avahi-resolve(1), avahi-daemon(8)

COMMENTS

This man page was written using xml2man(1) by Oliver Kurth.

Manuals

User

avahi-browse(1)