



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'avahi-daemon.8'***

**\$ man avahi-daemon.8**

avahi-daemon(8)

System Manager's Manual

avahi-daemon(8)

#### **NAME**

avahi-daemon - The Avahi mDNS/DNS-SD daemon

#### **SYNOPSIS**

avahi-daemon [options]

avahi-daemon --kill

avahi-daemon --reload

avahi-daemon --check

#### **DESCRIPTION**

The Avahi mDNS/DNS-SD daemon implements Apple's Zeroconf architecture (also known as "Ren? dezvous" or "Bonjour"). The daemon registers local IP addresses and static services using mDNS/DNS-SD and provides two IPC APIs for local programs to make use of the mDNS record cache the avahi-daemon maintains. First there is the so called "simple protocol" which is used exclusively by avahi-dnsconfd (a daemon which configures unicast DNS servers using server info published via mDNS) and nss-mdns (a libc NSS plugin, providing name resolution via mDNS). Finally there is the D-Bus interface which provides a rich object oriented interface to D-Bus enabled applications.

Upon startup avahi-daemon interprets its configuration file /etc/avahi/avahi-daemon.conf and reads XML fragments from /etc/avahi/services/\*.service which may define static DNS-SD services. If you enable publish-resolv-conf-dns-servers in avahi-daemon.conf the file /etc/resolv.conf will be read, too.

#### **OPTIONS**

-f | --file= FILE

Specify the configuration file to read. (default: /etc/avahi/avahi-daemon.conf)

**-D | --daemonize**

Daemonize after startup. Implies --syslog.

**-s | --syslog**

Log to syslog instead of STDERR. Implied by --daemonize.

**--debug**

Increase verbosity to debug level.

**--no-rlimits**

Don't enforce resource limits as specified in the configuration file. (See setrlimit(2) for more information)

**--no-drop-root**

Don't drop root privileges after startup and don't require daemon to be started as root. We recommend not to use this option.

**--no-chroot**

Don't chroot(2) the daemon. This option is only available when compiled with chroot() support.

**--no-proc-title**

Don't change the process name while running. Unless this option is specified avahi-daemon will reflect its current state and the selected host name in the process title.

**-k | --kill**

Kill an already running avahi-daemon. (equivalent to sending a SIGTERM)

**-r | --reload**

Tell an already running avahi-daemon to reread /etc/resolv.conf (in case you enabled publish-resolv-conf-dns-servers in avahi-daemon.conf) the files from /etc/avahi/services/. Please note that this will not reload the /etc/avahi/avahi-daemon.conf. (equivalent to sending a SIGHUP)

**-c | --check**

Return 0 as return code when avahi-daemon is already running.

**-h | --help**

Show help

**-v | --version**

Show version information

## FILES

/etc/avahi/avahi-daemon.conf: the default configuration file for avahi-daemon, avahi-daemon.conf(5) for more information.

/etc/avahi/hosts: additional static hostname mappings to publish in mDNS, see avahi.hosts(5) for more information.

/etc/avahi/services/\*.service: static service definitions, see avahi.service(5) for more information.

## SIGNALS

SIGINT, SIGTERM: avahi-daemon will shutdown. (Same as --kill).

SIGHUP: avahi-daemon will reload unicast DNS server data from /etc/resolv.conf and static service definitions from /etc/avahi/services/. (Same as --reload)

SIGUSR1: avahi-daemon will dump local and remote cached resource record data to syslog.

## AUTHORS

The Avahi Developers <avahi (at) lists (dot) freedesktop (dot) org>; Avahi is available from <http://avahi.org/>

## SEE ALSO

avahi-daemon.conf(5), avahi.hosts(5), avahi.service(5), avahi-dnsconfd(8), avahi-set-hostname(1)

<http://avahi.org/wiki/AvahiAndUnicastDotLocal> documents the problems when using Avahi in a unicast DNS zone .local.

## COMMENTS

This man page was written using xml2man(1) by Oliver Kurth.

Manuals

User

avahi-daemon(8)