



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'bswap.3'

\$ man bswap.3

BSWAP(3)

Linux Programmer's Manual

BSWAP(3)

NAME

bswap_16, bswap_32, bswap_64 - reverse order of bytes

SYNOPSIS

```
#include <byteswap.h>

bswap_16(x);
bswap_32(x);
bswap_64(x);
```

DESCRIPTION

These macros return a value in which the order of the bytes in their 2-, 4-, or 8-byte arguments is reversed.

RETURN VALUE

These macros return the value of their argument with the bytes reversed.

ERRORS

These macros always succeed.

CONFORMING TO

These macros are GNU extensions.

EXAMPLES

The program below swaps the bytes of the 8-byte integer supplied as its command-line argument. The following shell session demonstrates the use of the program:

```
$ ./a.out 0x0123456789abcdef
```

```
0x123456789abcdef ==> 0xefcdab8967452301
```

```
#include <stdio.h>
#include <stdint.h>
#include <stdlib.h>
#include <inttypes.h>
#include <byteswap.h>

int
main(int argc, char *argv[])
{
    uint64_t x;
    if (argc != 2) {
        fprintf(stderr, "Usage: %s <num>\n", argv[0]);
        exit(EXIT_FAILURE);
    }
    x = strtoull(argv[1], NULL, 0);
    printf("%#" PRIx64 " ==> %" PRIx64 "\n", x, bswap_64(x));
    exit(EXIT_SUCCESS);
}
```

SEE ALSO

[byteorder\(3\)](#), [endian\(3\)](#)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.