



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'buildah-manifest-add.1'

\$ man buildah-manifest-add.1

buildah-manifest-add(1) General Commands Manual buildah-manifest-add(1)

NAME

buildah-manifest-add - Add an image to a manifest list or image index.

SYNOPSIS

buildah manifest add listNameOrIndexName imageName

DESCRIPTION

Adds the specified image to the specified manifest list or image index.

RETURN VALUE

The list image's ID and the digest of the image's manifest.

OPTIONS

--all

If the image which should be added to the list or index is itself a list or index, add all of the contents to the local list. By default, only one image from such a list or index will be added to the list or index. Combining --all with any of the other options described below is NOT recommended.

--annotation annotation=value

Set an annotation on the entry for the newly-added image.

--arch

Override the architecture which the list or index records as a requirement for the image.

If imageName refers to a manifest list or image index, the architecture information will be retrieved from it. Otherwise, it will be retrieved from the image's configuration information.

--authfile path

Path of the authentication file. Default is \${XDG_RUNTIME_DIR}/containers/auth.json. If XDG_RUNTIME_DIR is not set, the default is /run/containers/\$UID/auth.json. This file is created using using buildah login.

If the authorization state is not found there, \$HOME/.docker/config.json is checked, which is set using docker login.

Note: You can also override the default path of the authentication file by setting the REGISTRY_AUTH_FILE environment variable. export REGISTRY_AUTH_FILE=path --cert-dir path

Use certificates at path (*.crt, *.cert, *.key) to connect to the registry. The default certificates directory is /etc/containers/certs.d.

--creds creds

The [username[:password]] to use to authenticate with the registry if required. If one or both values are not supplied, a command line prompt will appear and the value can be entered. The password is entered without echo.

--features

Specify the features list which the list or index records as requirements for the image.

This option is rarely used.

--os

Override the OS which the list or index records as a requirement for the image. If image? Name refers to a manifest list or image index, the OS information will be retrieved from it. Otherwise, it will be retrieved from the image's configuration information.

--os-features

Specify the OS features list which the list or index records as requirements for the image. This option is rarely used.

--os-version

Specify the OS version which the list or index records as a requirement for the image.

This option is rarely used.

--tls-verify bool-value

Require HTTPS and verification of certificates when talking to container registries (defaults to true). TLS verification cannot be used when talking to an insecure registry.

--variant

Specify the variant which the list or index records for the image. This option is typically used to distinguish between multiple entries which share the same architecture

value, but which expect different versions of its instruction set.

EXAMPLE

```
buildah manifest add mylist:v1.11 docker://fedora
506d8f4bb54931ea03a7e70173a0ed6302e3fb92dfadb3955ba5c17812e95c51:
sha256:f81f09918379d5442d20dff82a298f29698197035e737f76e511d5af422cabd7

buildah manifest add --all mylist:v1.11 docker://fedora
506d8f4bb54931ea03a7e70173a0ed6302e3fb92dfadb3955ba5c17812e95c51:
sha256:f81f09918379d5442d20dff82a298f29698197035e737f76e511d5af422cabd7

buildah manifest add --arch arm64 --variant v8 mylist:v1.11
docker://fedora@sha256:c829b1810d2dbb456e74a695fd3847530c8319e5a95dca623e9f1b1b89020d8b
506d8f4bb54931ea03a7e70173a0ed6302e3fb92dfadb3955ba5c17812e95c51:
sha256:c829b1810d2dbb456e74a695fd3847530c8319e5a95dca623e9f1b1b89020d8b
```

SEE ALSO

[buildah\(1\)](#), [buildah-login\(1\)](#), [buildah-manifest\(1\)](#), [buildah-manifest-create\(1\)](#), [buildah-manifest-remove\(1\)](#), [buildah-manifest-annotate\(1\)](#), [buildah-manifest-inspect\(1\)](#), [buildah-manifest-push\(1\)](#), [buildah-rmi\(1\)](#), [docker-login\(1\)](#)

buildah

September 2019

buildah-manifest-add(1)