



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'buildah-manifest-create.1'

\$ man buildah-manifest-create.1

buildah-manifest-create(1) General Commands Manual buildah-manifest-create(1)

NAME

buildah-manifest-create - Create a manifest list or image index.

SYNOPSIS

buildah manifest create listNameOrIndexName [imageName ...]

DESCRIPTION

Creates a new manifest list and stores it as an image in local storage using the specified name.

If additional images are specified, they are added to the newly-created list or index.

RETURN VALUE

The randomly-generated image ID of the newly-created list or index. The image can be deleted using the buildah rmi command.

OPTIONS

--all

If any of the images which should be added to the new list or index are themselves lists or indexes, add all of their contents. By default, only one image from such a list will be added to the newly-created list or index.

EXAMPLE

```
buildah manifest create mylist:v1.11
```

```
941c1259e4b85bebf23580a044e4838aa3c1e627528422c9bf9262ff1661fca9
```

```
buildah manifest create mylist:v1.11 docker://fedora
```

```
941c1259e4b85bebf23580a044e4838aa3c1e627528422c9bf9262ff1661fca9
```

```
buildah manifest create --all mylist:v1.11 docker://fedora
```

941c1259e4b85bebf23580a044e4838aa3c1e627528422c9bf9262ff1661fca9

SEE ALSO

[buildah\(1\)](#), [buildah-manifest\(1\)](#), [buildah-manifest-add\(1\)](#), [buildah-manifest-remove\(1\)](#),
[buildah-manifest-annotate\(1\)](#), [buildah-manifest-inspect\(1\)](#), [buildah-manifest-push\(1\)](#), [buil?](#)
[dah-rmi\(1\)](#)

[buildah](#)

September 2019

[buildah-manifest-create\(1\)](#)