



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'bzgrep.1'

\$ man bzgrep.1

BZGREP(1)

General Commands Manual

BZGREP(1)

NAME

bzgrep, bzfgrep, bzegrep - search possibly bzip2 compressed files for a regular expression

SYNOPSIS

bzgrep [grep_options] [-e] pattern filename...

bzegrep [egrep_options] [-e] pattern filename...

bzfgrep [fgrep_options] [-e] pattern filename...

DESCRIPTION

Bzgrep is used to invoke the grep on bzip2-compressed files. All options specified are passed directly to grep. If no file is specified, then the standard input is decompressed if necessary and fed to grep. Otherwise the given files are uncompressed if necessary and fed to grep.

If bzgrep is invoked as bzegrep or bzfgrep then egrep or fgrep is used instead of grep.

If the GREP environment variable is set, bzgrep uses it as the grep program to be invoked.

For example:

for sh: GREP=fgrep bzgrep string files

for csh: (setenv GREP fgrep; bzgrep string files)

AUTHOR

Charles Levert (charles@comm.polymtl.ca). Adapted to bzip2 by Philippe Troin <phil@fifi.org> for Debian GNU/Linux.

SEE ALSO

grep(1), egrep(1), fgrep(1), bzdiff(1), bzmore(1), bzless(1), bzip2(1)

BZGREP(1)