



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'catclose.3'

\$ man catclose.3

CATOPEN(3) Linux Programmer's Manual CATOPEN(3)

NAME

catopen, catclose - open/close a message catalog

SYNOPSIS

```
#include <nl_types.h>

nl_catd catopen(const char *name, int flag);

int catclose(nl_catd catalog);
```

DESCRIPTION

The function `catopen()` opens a message catalog and returns a catalog descriptor. The descriptor remains valid until `catclose()` or `execve(2)`. If a file descriptor is used to implement catalog descriptors, then the `FD_CLOEXEC` flag will be set.

The argument `name` specifies the name of the message catalog to be opened. If `name` specifies an absolute path (i.e., contains a '/'), then `name` specifies a pathname for the message catalog. Otherwise, the environment variable `NLSPATH` is used with `name` substituted for `%N` (see `locale(7)`). It is unspecified whether `NLSPATH` will be used when the process has root privileges. If `NLSPATH` does not exist in the environment, or if a message catalog cannot be opened in any of the paths specified by it, then an implementation-defined path is used. This latter default path may depend on the `LC_MESSAGES` locale setting when the flag argument is `NL_CAT_LOCALE` and on the `LANG` environment variable when the flag argument is 0. Changing the `LC_MESSAGES` part of the locale may invalidate open catalog descriptors.

The flag argument to `catopen()` is used to indicate the source for the language to use. If it is set to `NL_CAT_LOCALE`, then it will use the current locale setting for `LC_MESSAGES`.

Otherwise, it will use the LANG environment variable.

The function `catclose()` closes the message catalog identified by `catalog`. It invalidates any subsequent references to the message catalog defined by `catalog`.

RETURN VALUE

The function `catopen()` returns a message catalog descriptor of type `nl_catd` on success.

On failure, it returns `(nl_catd) -1` and sets `errno` to indicate the error. The possible error values include all possible values for the `open(2)` call.

The function `catclose()` returns 0 on success, or -1 on failure.

ENVIRONMENT

LC_MESSAGES

May be the source of the LC_MESSAGES locale setting, and thus determine the language to use if flag is set to `NL_CAT_LOCALE`.

LANG The language to use if flag is 0.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?`catopen()` ? Thread safety ? MT-Safe env ?

??

?`catclose()` ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

NOTES

The above is the POSIX.1 description. The glibc value for `NL_CAT_LOCALE` is 1. The default fault path varies, but usually looks at a number of places below `/usr/share/locale`.

SEE ALSO

`catgets(3)`, `setlocale(3)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

