



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'catman.8'

\$ man catman.8

CATMAN(8)

Manual pager utils

CATMAN(8)

NAME

catman - create or update the pre-formatted manual pages

SYNOPSIS

catman [-d?V] [-M path] [-C file] [section] ...

DESCRIPTION

catman is used to create an up to date set of pre-formatted manual pages known as cat pages. Cat pages are generally much faster to display than the original manual pages, but require extra storage space. The decision to support cat pages is that of the local administrator, who must provide suitable directories to contain them.

The options available to catman are the manual page hierarchies and sections to pre-format. The default hierarchies are those specified as system hierarchies in the man-db configuration file, and the default sections are either the colon-delimited contents of the environment variable \$MANSECT or the standard set compiled into man if \$MANSECT is undefined. Supplying catman with a set of whitespace-delimited section names will override both of the above.

catman makes use of the index database cache associated with each hierarchy to determine which files need to be formatted.

OPTIONS

-d, --debug

Print debugging information.

-M path, --manpath=path

Specify an alternate colon-delimited manual page hierarchy search path. By default

fault, this is all paths indicated as system hierarchies in the man-db configuration file.

-C file, --config-file=file

Use this user configuration file rather than the default of `~/.manpath`.

-?, --help

Print a help message and exit.

--usage

Print a short usage message and exit.

-V, --version

Display version information.

ENVIRONMENT

MANSECT

If `$MANSECT` is set, its value is a colon-delimited list of sections and it is used to determine which manual sections to search and in what order. The default is "1 n l 8 3 0 2 3posix 3pm 3perl 3am 5 4 9 6 7", unless overridden by the `SECTION` directive in `/etc/manpath.config`.

MANPATH

If `$MANPATH` is set, its value is interpreted as the colon-delimited manual page hierarchy search path to use.

See the `SEARCH PATH` section of `manpath(5)` for the default behaviour and details of how this environment variable is handled.

FILES

`/etc/manpath.config`

man-db configuration file.

`/usr/man/index.(bt|db|dir|pag)`

A traditional global index database cache.

`/var/catman/index.(bt|db|dir|pag)`

An alternate or FSSTND compliant global index database cache.

SEE ALSO

`man(1)`, `manpath(5)`, `mandb(8)`

AUTHOR

Wilf. (`G.Wilford@ee.surrey.ac.uk`).

Fabrizio Polacco (`fpolacco@debian.org`).

Colin Watson (cjwatson@debian.org).

BUGS

<https://gitlab.com/cjwatson/man-db/-/issues>

<https://savannah.nongnu.org/bugs/?group=man-db>

2.10.2

2022-03-17

CATMAN(8)