

CHROOT(8)

User Commands

CHROOT(8)

NAME

chroot - run command or interactive shell with special root directory

SYNOPSIS

chroot [OPTION] NEWROOT [COMMAND [ARG]...]

chroot OPTION

DESCRIPTION

Run **COMMAND** with root directory set to **NEWROOT**.

--groups=G_LIST

specify supplementary groups as **g1,g2,...,gN**

--userspec=USER:GROUP

specify user and group (ID or name) to use

--skip-chdir

do not change working directory to **'/'**

--help display this help and exit

--version

If no command is given, run "\$SHELL" -i (default: '/bin/sh -i').

Exit status:

- 125 if the chroot command itself fails
- 126 if COMMAND is found but cannot be invoked
- 127 if COMMAND cannot be found
- the exit status of COMMAND otherwise

AUTHOR

Written by Roland McGrath.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright ? 2023 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

Linux UBUNTU Manual Pages

SEE ALSO

chroot(2)

Full documentation <<https://www.gnu.org/software/coreutils/chroot>>

or available locally via: info '(coreutils) chroot invocation'

GNU coreutils 9.4

June 2025

CHROOT(8)