



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'cloud-id.1'

\$ man cloud-id.1

CLOUD-ID(1) General Commands Manual CLOUD-ID(1)

NAME

cloud-id - Report the canonical cloud-id for this instance

SYNOPSIS

cloud-id [-h] [-j] [-l] [-i <INSTANCE_DATA>]

DESCRIPTION

cloud-id is the lowercase name of the cloud datasource discovered.

The cloud-id will be 'not run' when systemd generator has not run yet. The cloud-id will be 'disabled' when cloud-init is disabled or when ds-identify did not find a valid data? source.

See cloud-init status --long for more information.

OPTIONS

-h, --help

Show help message and exit

-j, --json

Report all standardized cloud-id information as json

-l, --long

Report extended cloud-id information as tab-delimited string

-i <data>, --instance-data <data>

Path to instance-data.json file. Default is /run/cloud-init/instance-data.json

EXIT STATUS

0 On success

1 Due to an error

2 Due to cloud-init in a disabled state. See: `cloud-init status --long`

3 The cloud-init generator and discovery has not yet run.

COPYRIGHT

Copyright (C) 2021 Canonical Ltd. License GPL-3 or Apache-2.0

SEE ALSO

Full documentation at: <https://cloudinit.readthedocs.io>

CLOUD-ID(1)