



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'containers-mounts.conf.5'

\$ man containers-mounts.conf.5

containers-mounts.conf(5)()

containers-mounts.conf(5)()

NAME

containers-mounts.conf - configuration file for default mounts in containers

DESCRIPTION

The mounts.conf file specifies volume mount directories that are automatically mounted in? side containers. Container processes can then use this content. Usually these directories are used for passing secrets or credentials required by the package software to access re? mote package repositories. Note that for security reasons, tools adhering to the mounts.conf are expected to copy the contents instead of bind mounting the paths from the host.

FORMAT

The format of the mounts.conf is the volume format /SRC:/DEST, one mount per line. For ex? ample, a mounts.conf with the line /usr/share/secrets:/run/secrets would cause the con? tents of the /usr/share/secrets directory on the host to be mounted on the /run/secrets directory inside the container. Setting mountpoints allows containers to use the files of the host, for instance, to use the host's subscription to some enterprise Linux distribu? tion.

FILES

Some distributions may provide a /usr/share/containers/mounts.conf file to provide default mounts, but users can create a /etc/containers/mounts.conf, to specify their own special volumes to mount in the container. When Podman runs in rootless mode, the file \$HOME/.con? fig/containers/mounts.conf will override the default if it exists.

HISTORY

Aug 2018, Originally compiled by Valentin Rothberg vrothberg@suse.com ?mailto:vroth?

berg@suse.com?

containers-mounts.conf(5)()