



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'dcb.8'***

**\$ man dcb.8**

DCB(8) Linux DCB(8)

#### **NAME**

dcb - show / manipulate DCB (Data Center Bridging) settings

#### **SYNOPSIS**

dcb [ OPTIONS ] { app | buffer | ets | maxrate | pfc } { COMMAND | help }

dcb [ -force ] -batch filename

dcb [ OPTIONS ] help

#### **OPTIONS**

-n, --netns <NETNS>

switches dcb to the specified network namespace NETNS.

-V, --Version

Print the version of the dcb utility and exit.

-b, --batch <FILENAME>

Read commands from provided file or standard input and invoke them. First failure will cause termination of dcb.

-f, --force

Don't terminate dcb on errors in batch mode. If there were any errors during execution of the commands, the application return code will be non zero.

-i, --iec

When showing rates, use ISO/IEC 1024-based prefixes (Ki, Mi, Bi) instead of the 1000-based ones (K, M, B).

-j, --json

Generate JSON output.

**-N, --Numeric**

If the subtool in question translates numbers to symbolic names in some way, sup? press this translation.

**-p, --pretty**

When combined with **-j** generate a pretty JSON output.

**-s, --statistics**

If the object in question contains any statistical counters, show them as part of the "show" output.

## OBJECTS

**app** - Configuration of application priority table

**buffer** - Configuration of port buffers

**ets** - Configuration of ETS (Enhanced Transmission Selection)

**maxrate**

- Configuration of per-TC maximum transmit rate

**pfc** - Configuration of PFC (Priority-based Flow Control)

## COMMANDS

A COMMAND specifies the action to perform on the object. The set of possible actions depends on the object type. As a rule, it is possible to show objects and to invoke topical help, which prints a list of available commands and argument syntax conventions.

## ARRAY PARAMETERS

Like commands, specification of parameters is in the domain of individual objects (and their commands) as well. However, much of the DCB interface revolves around arrays of fixed size that specify one value per some key, such as per traffic class or per priority.

There is therefore a single syntax for adjusting elements of these arrays. It consists of a series of KEY:VALUE pairs, where the meaning of the individual keys and values depends on the parameter.

The elements are evaluated in order from left to right, and the latter ones override the earlier ones. The elements that are not specified on the command line are queried from the kernel and their current value is retained.

As an example, take a made-up parameter `tc-juju`, which can be set to charm traffic in a given TC with either good luck or bad luck. KEY can therefore be 0..7 (as is usual for TC numbers in DCB), and VALUE either of none, good, and bad. An example of changing a juju value of TCs 0 and 7, while leaving all other intact, would then be:

```
# dcb foo set dev eth0 tc-juju 0:good 7:bad
```

A special key, `all`, is recognized which sets the same value to all array elements. This can be combined with the usual single-element syntax. E.g. in the following, the `juju` of all keys is set to `none`, except 0 and 7, which have other values:

```
# dcb foo set dev eth0 tc-juju all:none 0:good 7:bad
```

## EXIT STATUS

Exit status is 0 if command was successful or a positive integer upon failure.

## SEE ALSO

`dcb-app(8)`, `dcb-buffer(8)`, `dcb-ets(8)`, `dcb-maxrate(8)`, `dcb-pfc(8)`

## REPORTING BUGS

Report any bugs to the Network Developers mailing list <[netdev@vger.kernel.org](mailto:netdev@vger.kernel.org)> where the development and maintenance is primarily done. You do not have to be subscribed to the list to send a message there.

## AUTHOR

Petr Machata <[me@pmachata.org](mailto:me@pmachata.org)>

iproute2

19 October 2020

DCB(8)