



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'difftime.3'

\$ man difftime.3

DIFFTIME(3)

Linux Programmer's Manual

DIFFTIME(3)

NAME

difftime - calculate time difference

SYNOPSIS

```
#include <time.h>

double difftime(time_t time1, time_t time0);
```

DESCRIPTION

The `difftime()` function returns the number of seconds elapsed between time `time1` and time `time0`, represented as a double. Each of the times is specified in calendar time, which means its value is a measurement (in seconds) relative to the Epoch, 1970-01-01 00:00:00 +0000 (UTC).

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?`difftime()` ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C89, C99, SVr4, 4.3BSD.

NOTES

On a POSIX system, `time_t` is an arithmetic type, and one could just define

```
#define difftime(t1,t0) (double)(t1 - t0)
```

when the possible overflow in the subtraction is not a concern.

SEE ALSO

`date(1)`, `gettimeofday(2)`, `time(2)`, `ctime(3)`, `gmtime(3)`, `localtime(3)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2015-08-08

DIFFTIME(3)