



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'dir.1'

\$ man dir.1

DIR(1) User Commands DIR(1)

NAME

dir - list directory contents

SYNOPSIS

dir [OPTION]... [FILE]...

DESCRIPTION

List information about the FILEs (the current directory by default). Sort entries alpha?

betically if none of -cftuvSUX nor --sort is specified.

Mandatory arguments to long options are mandatory for short options too.

-a, --all

do not ignore entries starting with .

-A, --almost-all

do not list implied . and ..

--author

with -l, print the author of each file

-b, --escape

print C-style escapes for nongraphic characters

--block-size=SIZE

with -l, scale sizes by SIZE when printing them; e.g., '--block-size=M'; see SIZE

format below

-B, --ignore-backups

do not list implied entries ending with ~

-c with -lt: sort by, and show, ctime (time of last modification of file status infor?

mation); with -l: show ctime and sort by name; otherwise: sort by ctime, newest first

-C list entries by columns

--color[=WHEN]

colorize the output; WHEN can be 'always' (default if omitted), 'auto', or 'never';

more info below

-d, --directory

list directories themselves, not their contents

-D, --dired

generate output designed for Emacs' dired mode

-f do not sort, enable -aU, disable -ls --color

-F, --classify

append indicator (one of */=>@|) to entries

--file-type

likewise, except do not append '*'

--format=WORD

across -x, commas -m, horizontal -x, long -l, single-column -1, verbose -l, verti?

cal -C

--full-time

like -l --time-style=full-iso

-g like -l, but do not list owner

--group-directories-first

group directories before files;

can be augmented with a --sort option, but any use of --sort=none (-U) disables grouping

-G, --no-group

in a long listing, don't print group names

-h, --human-readable

with -l and -s, print sizes like 1K 234M 2G etc.

--si likewise, but use powers of 1000 not 1024

-H, --dereference-command-line

follow symbolic links listed on the command line

--dereference-command-line-symlink-to-dir

follow each command line symbolic link

that points to a directory

`--hide=PATTERN`

do not list implied entries matching shell PATTERN (overridden by `-a` or `-A`)

`--hyperlink[=WHEN]`

hyperlink file names; WHEN can be 'always' (default if omitted), 'auto', or 'never'

`--indicator-style=WORD`

append indicator with style WORD to entry names: none (default), slash (`-p`),

file-type (`--file-type`), classify (`-F`)

`-i`, `--inode`

print the index number of each file

`-I`, `--ignore=PATTERN`

do not list implied entries matching shell PATTERN

`-k`, `--kibibytes`

default to 1024-byte blocks for disk usage; used only with `-s` and per directory to?

tals

`-l` use a long listing format

`-L`, `--dereference`

when showing file information for a symbolic link, show information for the file

the link references rather than for the link itself

`-m` fill width with a comma separated list of entries

`-n`, `--numeric-uid-gid`

like `-l`, but list numeric user and group IDs

`-N`, `--literal`

print entry names without quoting

`-o` like `-l`, but do not list group information

`-p`, `--indicator-style=slash`

append / indicator to directories

`-q`, `--hide-control-chars`

print ? instead of nongraphic characters

`--show-control-chars`

show nongraphic characters as-is (the default, unless program is 'ls' and output is

a terminal)

-Q, --quote-name

enclose entry names in double quotes

--quoting-style=WORD

use quoting style WORD for entry names: literal, locale, shell, shell-always, shell-escape, shell-escape-always, c, escape (overrides QUOTING_STYLE environment variable)

-r, --reverse

reverse order while sorting

-R, --recursive

list subdirectories recursively

-s, --size

print the allocated size of each file, in blocks

-S sort by file size, largest first

--sort=WORD

sort by WORD instead of name: none (-U), size (-S), time (-t), version (-v), extension (-X)

--time=WORD

change the default of using modification times; access time (-u): atime, access, use; change time (-c): ctime, status; birth time: birth, creation; with -l, WORD determines which time to show; with --sort=time, sort by WORD (newest first)

--time-style=TIME_STYLE

time/date format with -l; see TIME_STYLE below

-t sort by time, newest first; see --time

-T, --tabsize=COLS

assume tab stops at each COLS instead of 8

-u with -lt: sort by, and show, access time; with -l: show access time and sort by name; otherwise: sort by access time, newest first

-U do not sort; list entries in directory order

-v natural sort of (version) numbers within text

-w, --width=COLS

set output width to COLS. 0 means no limit

-x list entries by lines instead of by columns

-X sort alphabetically by entry extension

-Z, --context

print any security context of each file

-1 list one file per line. Avoid '\n' with -q or -b

--help display this help and exit

--version

output version information and exit

The SIZE argument is an integer and optional unit (example: 10K is 10*1024). Units are K,M,G,T,P,E,Z,Y (powers of 1024) or KB,MB,... (powers of 1000). Binary prefixes can be used, too: KiB=K, MiB=M, and so on.

The TIME_STYLE argument can be full-iso, long-iso, iso, locale, or +FORMAT. FORMAT is interpreted like in date(1). If FORMAT is FORMAT1<newline>FORMAT2, then FORMAT1 applies to non-recent files and FORMAT2 to recent files. TIME_STYLE prefixed with 'posix-' takes effect only outside the POSIX locale. Also the TIME_STYLE environment variable sets the default style to use.

Using color to distinguish file types is disabled both by default and with --color=never.

With --color=auto, ls emits color codes only when standard output is connected to a terminal. The LS_COLORS environment variable can change the settings. Use the dircolors command to set it.

Exit status:

- 0 if OK,
- 1 if minor problems (e.g., cannot access subdirectory),
- 2 if serious trouble (e.g., cannot access command-line argument).

AUTHOR

Written by Richard M. Stallman and David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright ? 2020 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation <<https://www.gnu.org/software/coreutils/dir>>

or available locally via: info '(coreutils) dir invocation'

GNU coreutils 8.32

February 2024

DIR(1)