



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'dmmp_flush_mpath.3'

\$ man dmmp_flush_mpath.3

dmmp_flush_mpath(3) Device Mapper Multipath API - libdmmp Manual dmmp_flush_mpath(3)

NAME

dmmp_flush_mpath - Flush specified multipath device map if unused.

SYNOPSIS

int dmmp_flush_mpath (struct dmmp_context *ctx, const char *mpath_name);

ARGUMENTS

ctx Pointer of 'struct dmmp_context'. If this pointer is NULL, your program will be terminated by assert.

mpath_name const char *. The name of multipath device map.

DESCRIPTION

Flush a multipath device map specified as parameter, if unused.

RETURN

int. Valid error codes are:

* DMMP_OK

* DMMP_ERR_BUG

* DMMP_ERR_NO_MEMORY

* DMMP_ERR_NO_DAEMON

* DMMP_ERR_MPATH_BUSY

* DMMP_ERR_MPATH_NOT_FOUND

* DMMP_ERR_INVALID_ARGUMENT

* DMMP_ERR_PERMISSION_DENY

Error number could be converted to string by dmmp_strerror.

March 2018

dmmp_flush_mpath

dmmp_flush_mpath(3)