



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'docker-pod-stop.1'

\$ man docker-pod-stop.1

podman-pod-stop(1())

NAME

podman-pod-stop - Stop one or more pods

SYNOPSIS

podman pod stop [options] pod ...

DESCRIPTION

Stop containers in one or more pods. You may use pod IDs or names as input.

OPTIONS

--all, -a

Stops all pods

--ignore, -i

Ignore errors when specified pods are not in the container store. A user might have decided to manually remove a pod which would lead to a failure during the ExecStop directive of a systemd service referencing that pod.

--latest, -l

Instead of providing the pod name or ID, stop the last created pod. (This option is not available with the remote Podman client)

--time, -t=time

Timeout to wait before forcibly stopping the containers in the pod.

--pod-id-file

Read pod ID from the specified file and stop the pod. Can be specified multiple times.

EXAMPLE

Stop a pod called mywebserverpod

```
$ podman pod stop mywebserverpod
```

```
cc8f0bea67b1a1a11aec1ecd38102a1be4b145577f21fc843c7c83b77fc28907
```

Stop two pods by their short IDs.

```
$ podman pod stop 490eb 3557fb
```

```
490eb241aaf704d4dd2629904410fe4aa31965d9310a735f8755267f4ded1de5
```

```
3557fbea6ad61569de0506fe037479bd9896603c31d3069a6677f23833916fab
```

Stop the most recent pod

```
$ podman pod stop --latest
```

```
3557fbea6ad61569de0506fe037479bd9896603c31d3069a6677f23833916fab
```

Stop all pods

```
$ podman pod stop --all
```

```
19456b4cd557eaf9629825113a552681a6013f8c8cad258e36ab825ef536e818
```

```
3557fbea6ad61569de0506fe037479bd9896603c31d3069a6677f23833916fab
```

```
490eb241aaf704d4dd2629904410fe4aa31965d9310a735f8755267f4ded1de5
```

```
70c358daecf71ef9be8f62404f926080ca0133277ef7ce4f6aa2d5af6bb2d3e9
```

```
cc8f0bea67b1a1a11aec1ecd38102a1be4b145577f21fc843c7c83b77fc28907
```

Stop two pods via --pod-id-file

```
$ podman pod stop --pod-id-file file1 --pod-id-file file2
```

```
19456b4cd557eaf9629825113a552681a6013f8c8cad258e36ab825ef536e818
```

```
cc8f0bea67b1a1a11aec1ecd38102a1be4b145577f21fc843c7c83b77fc28907
```

Stop all pods with a timeout of 1 second.

```
$ podman pod stop -a -t 1
```

```
3557fbea6ad61569de0506fe037479bd9896603c31d3069a6677f23833916fab
```

```
490eb241aaf704d4dd2629904410fe4aa31965d9310a735f8755267f4ded1de5
```

```
70c358daecf71ef9be8f62404f926080ca0133277ef7ce4f6aa2d5af6bb2d3e9
```

SEE ALSO

podman-pod(1), podman-pod-start(1), podman-stop(1)

HISTORY

July 2018, Originally compiled by Peter Hunt pehunt@redhat.com ?mailto:pehunt@redhat.com?

podman-pod-stop(1)()