



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'dpkg-realpath.1'

\$ man dpkg-realpath.1

dpkg-realpath(1)

NAME

dpkg-realpath - print the resolved pathname with DPKG_ROOT support

SYNOPSIS

dpkg-realpath [option...] pathname

DESCRIPTION

dpkg-realpath is a tool (since dpkg 1.20.1) to resolve a pathname, that takes the dpkg(1) root directory into account, either implicitly from the DPKG_ROOT environment variable or from the command-line --root or --instdir options, and returns an absolute pathname relative to the root directory. The root directory must not be prefixed to the pathname to be resolved.

This is intended to be used by other dpkg helpers, or by maintainer scripts instead of using realpath(1) or readlink(1) to canonicalize pathnames, as these latter commands do not support canonicalization relative to a different root than /.

OPTIONS

-z, --zero

Use a NUL byte to end output lines instead of a new line character (since dpkg 1.20.6)

--instdir directory

--root directory

Set the root directory to directory, which is the base directory that pathnames get canonicalized against. Defaults to ?/?.

-?, --help

Show the usage message and exit.

--version

Show the version and exit.

ENVIRONMENT

DPKG_ROOT

If set and the --installdir or --root options have not been specified, it will be used as the filesystem root directory.

DPKG_COLORS

Sets the color mode. The currently accepted values are: auto (default), always and never.

SEE ALSO

[realpath\(1\)](#), [readlink\(1\)](#).

1.21.1

2024-02-23

[dpkg-realpath\(1\)](#)