



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'erb3.0.1'

\$ man erb3.0.1

ERB(1) Ruby Programmer's Reference Guide ERB(1)

NAME

erb ? Ruby Templating

SYNOPSIS

erb [--version] [-UPdnvx] [-E ext[:int]] [-S level] [-T mode] [-r library] [--] [file ...]

DESCRIPTION

erb is a command line front-end for ERB library, which is an implementation of eRuby.

ERB provides an easy to use but powerful templating system for Ruby. Using ERB, actual Ruby

code can be added to any plain text document for the purposes of generating document infor?

mation details and/or flow control.

erb is a part of Ruby.

OPTIONS

--version Prints the version of erb.

-E external[:internal]

--encoding external[:internal]

Specifies the default value(s) for external encodings and internal encoding.

Values should be separated with colon (:).

You can omit the one for internal encodings, then the value

(Encoding.default_internal) will be nil.

-P Disables ruby code evaluation for lines beginning with %.

-S level Specifies the safe level in which eRuby script will run.

-T mode Specifies trim mode (default 0). mode can be one of

0 EOL remains after the embedded ruby script is evaluated.

- 1 EOL is removed if the line ends with %>.
- 2 EOL is removed if the line starts with <% and ends with %>.
- EOL is removed if the line ends with -%>. And leading white?
spaces are removed if the erb directive starts with <%-.

-r Load a library

-U can be one of Sets the default value for internal encodings
(Encoding.default_internal) to UTF-8.

-d

--debug Turns on debug mode. \$DEBUG will be set to true.

-h

--help Prints a summary of the options.

-n Used with -x. Prepends the line number to each line in the output.

-v Enables verbose mode. \$VERBOSE will be set to true.

-x Converts the eRuby script into Ruby script and prints it without line numbers.

EXAMPLES

Here is an eRuby script

```
<?xml version="1.0" ?>

<% require 'prime' -%>

<erb-example>

  <calc><%= 1+1 %></calc>

  <var><%= __FILE__ %></var>

  <library><%= Prime.each(10).to_a.join(", ") %></library>

</erb-example>
```

Command

```
% erb -T - example.erb
```

prints

```
<?xml version="1.0" ?>

<erb-example>

  <calc>2</calc>

  <var>example.erb</var>

  <library>2, 3, 5, 7</library>

</erb-example>
```

SEE ALSO

`ruby(1)`.

And see `ri(1)` documentation for `ERB` class.

REPORTING BUGS

- ? Security vulnerabilities should be reported via an email to security@ruby-lang.org. Reported problems will be published after being fixed.
- ? Other bugs and feature requests can be reported via the Ruby Issue Tracking System (<https://bugs.ruby-lang.org/>). Do not report security vulnerabilities via this system because it publishes the vulnerabilities immediately.

AUTHORS

Written by Masatoshi SEKI.

UNIX

December 16, 2018

UNIX