



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'execvp.3'

\$ man exec/p.3

EXEC(3) Linux Programmer's Manual EXEC(3)

NAME

`execl, execlp, execle, execv, execvp, execvpe` - execute a file

SYNOPSIS

```
#include <unistd.h>

extern char **environ;

int execl(const char *pathname, const char *arg, ...

        /* (char *) NULL */);

int execlp(const char *file, const char *arg, ...

        /* (char *) NULL */);

int execle(const char *pathname, const char *arg, ...

        /* (char *) NULL, char *const envp[] */);

int execv(const char *pathname, char *const argv[]);

int execvp(const char *file, char *const argv[]);

int execvpe(const char *file, char *const argv[],

            char *const envp[]);
```

Feature Test Macro Requirements for glibc (see [feature_test_macros\(7\)](#)):

execvpe(): GNU SOURCE

DESCRIPTION

The `exec()` family of functions replaces the current process image with a new process image. The functions described in this manual page are layered on top of `execve(2)`. (See the manual page for `execve(2)` for further details about the replacement of the current process image.)

The initial argument for these functions is the name of a file that is to be executed.

The functions can be grouped based on the letters following the "exec" prefix.

I - execl(), execl(), execle()

The const char *arg and subsequent ellipses can be thought of as arg0, arg1, ..., argn.

Together they describe a list of one or more pointers to null-terminated strings that represent the argument list available to the executed program. The first argument, by convention, should point to the filename associated with the file being executed. The list of arguments must be terminated by a null pointer, and, since these are variadic functions, this pointer must be cast (char *) NULL.

By contrast with the 'l' functions, the 'v' functions (below) specify the command-line arguments of the executed program as a vector.

V - execv(), execvp(), execvpe()

The char *const argv[] argument is an array of pointers to null-terminated strings that represent the argument list available to the new program. The first argument, by convention, should point to the filename associated with the file being executed. The array of pointers must be terminated by a null pointer.

E - execle(), execvpe()

The environment of the caller is specified via the argument envp. The envp argument is an array of pointers to null-terminated strings and must be terminated by a null pointer.

All other exec() functions (which do not include 'e' in the suffix) take the environment for the new process image from the external variable environ in the calling process.

P - execlp(), execvp(), execvpe()

These functions duplicate the actions of the shell in searching for an executable file if the specified filename does not contain a slash (/) character. The file is sought in the colon-separated list of directory pathnames specified in the PATH environment variable.

If this variable isn't defined, the path list defaults to a list that includes the directories returned by confstr(_CS_PATH) (which typically returns the value "/bin:/usr/bin") and possibly also the current working directory; see NOTES for further details.

If the specified filename includes a slash character, then PATH is ignored, and the file at the specified pathname is executed.

In addition, certain errors are treated specially.

If permission is denied for a file (the attempted execve(2) failed with the error EACCES), these functions will continue searching the rest of the search path. If no other file is

found, however, they will return with errno set to EACCES.

If the header of a file isn't recognized (the attempted execve(2) failed with the error ENOEXEC), these functions will execute the shell (/bin/sh) with the path of the file as its first argument. (If this attempt fails, no further searching is done.)

All other exec() functions (which do not include 'p' in the suffix) take as their first argument a (relative or absolute) pathname that identifies the program to be executed.

RETURN VALUE

The exec() functions return only if an error has occurred. The return value is -1, and errno is set to indicate the error.

ERRORS

All of these functions may fail and set errno for any of the errors specified for execve(2).

VERSIONS

The execvpe() function first appeared in glibc 2.11.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?exec(), execle(), execv() ? Thread safety ? MT-Safe ?

??

?execvp(), execvvp(), execvpe() ? Thread safety ? MT-Safe env ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

The execvpe() function is a GNU extension.

NOTES

The default search path (used when the environment does not contain the variable PATH) shows some variation across systems. It generally includes /bin and /usr/bin (in that order) and may also include the current working directory. On some other systems, the current working directory is included after /bin and /usr/bin, as an anti-Trojan-horse measure. The glibc implementation long followed the traditional default where the current working directory is included at the start of the search path. However, some code refactoring during the development of glibc 2.30 removed this behavior, and the current behavior is to search the current working directory first, then /bin and /usr/bin. This change was made to improve security by preventing attacks that rely on the traditional search order.

ing the development of glibc 2.24 caused the current working directory to be dropped alto?gether from the default search path. This accidental behavior change is considered mildly beneficial, and won't be reverted.

The behavior of `execvp()` when errors occur while attempting to execute the file is historic practice, but has not traditionally been documented and is not specified by the POSIX standard. BSD (and possibly other systems) do an automatic sleep and retry if `ETXTBSY` is encountered. Linux treats it as a hard error and returns immediately.

Traditionally, the functions `execvp()` and `execv()` ignored all errors except for the ones described above and `ENOMEM` and `E2BIG`, upon which they returned. They now return if any error other than the ones described above occurs.

BUGS

Before glibc 2.24, `execl()` and `execle()` employed `realloc(3)` internally and were consequently not async-signal-safe, in violation of the requirements of POSIX.1. This was fixed in glibc 2.24.

Architecture-specific details

On sparc and sparc64, `execv()` is provided as a system call by the kernel (with the prototype shown above) for compatibility with SunOS. This function is not employed by the `execv()` wrapper function on those architectures.

SEE ALSO

`sh(1)`, `execve(2)`, `execveat(2)`, `fork(2)`, `ptrace(2)`, `fexecve(3)`, `system(3)`, `environ(7)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.